

NAVAL POSTGRADUATE SCHOOL Monterey, California





THESIS

PRIORITIZATION OF ADVANCED BASE FUNCTIONAL COMPONENTS

рy

Linda A. Guadalupe

September 1988

Thesis Advisor:

Samuel H. Parry

Approved for public release; distribution is unlimited

SECURITY CLASSIFICATION OF THIS PAGE					
	REPORT DOCU	MENTATION I	PAGE		
1. REPORT SECURITY CLASSIFICATION UNCLASSIFIED		16 RESTRICTIVE	MARKINGS		and of the second se
24. SECURITY CLASSIFICATION AUTHORITY	mendingstylende vogster er egen het bier sid Differen en men. De ende vog tilbligde	3 DISTRIBUTION / AVAILABILITY OF REPORT			
2b. DECLASSIFICATION / DOWNGRADING SCHEDU	ILE	Approved for public release; Distribution is unlimited.			
4. PERFORMING ORGANIZATION REPORT NUMBE	R(S)	5 MONITORING C	RGANIZATION R	EPORT NUMB	BER(S)
6a NAME OF PERFORMING ORGANIZATION	66 OFFICE SYMBOL	78 NAME OF MO	NITORING ORGA	NIZATION	
Naval Postgraduate Schoo	(If applicable)	Naval Postgraduate School			
6c. ADDRESS (City, State, and ZIP Code)		7b. ADDRESS (City, State, and ZIP Code)			
Monterey, California 93	943-5000	Monter	ey, Calif	ornia 9	3943-5000
88. NAME OF FUNDING SPONSORING ORGANIZATION	8b OFFICE SYMBOL (If applicable)	9. PROCUREMENT INSTRUMENT IDENTIFICATION NUMBER			
8c. ADDRESS (City, State, and ZIP Code)	Angele and the second second little and a second second second	10 SOURCE OF FL	UNDING NUMBER	(5	
		PROGRAM ELEMENT NO.	PROJECT NO	TASK NO	WORK UNIT ACCESSION N
11 TITLE (Include Security Classification) Price 12 PERSONAL AUTHOR(S)	Com	f Advanced ponents Guadalupe	Base Fund	ctional	
Master's Thesis 16 SUPPLEMENTARY NOTATION The view and do not reflect the off Defense or the U.S. Govern	vs expressed Ficial policy	September in this the or position	1988 esis are	those of	117 the autho
17 COSATI CODES	(18 SUBJECT TERMS (
FIELD GROUP SUB-GROUP	Advanced Ba Pairwise Con (AHP), Cate	nnarisons/A	halutical	Hiorar	ohy Dreson
19 ABSTRACT (Continue on reverse if necessary	and identify by block n	umber) This			
of two analytical method Advanced Base Functiona importance to mission accommentioned by the Fleet requirements were rated judgments and the other examining the results of one-time relative ranking the differences in scope provides a foundation quantitative measurements which can be used as aids 20 DISTRIBUTION: AVAILABILITY OF ABSTRACT TO UNCLASSIFIED/UNLIMITED SAME AS R	l Components complishment ifically, ele Commanders-in in two surv using a me using these as of the ABFG and applicat for furthe of the need to decision	ing a prior (ABFCs) we during the even of the condition select	rity rank vith regard early date and the compare two teams to obtain the budge unity (LASSIFICA FIED	ing of and to any of a most free most ing cat mpariso y: 1) and 2) of a hniques are measured.	relative a general requently turgent regorical ons. In provides describes , and 3) aningful surements rocess.
Prof. Samuel H. Parry		(408) 646			Ру
DD FORM 1473, 84 MAR 83 AP	Redition may be used unt All other editions are ob		SECURITY (CLASSIF CATIO	N OF THIS PAGE

Approved for public release; distribution is unlimited

Prioritization of Advanced Base Functional Components

by

Linda A. Guadalupe Lieu enant Commander, United States Navy B.S., Fairleigh Dickinson University, 1977

Submitted in partial fulfillment of the requirements for the degree of

MASTER OF SCIENCE IN OPERATIONS RESEARCH

from the

NAVAL POSTGRADUATE SCHOOL September 1988

Author:	Linda a Guadalupe
	Linda A. Guadalupe
Approved by:	Samuel H. Parry, Thesis Advisor
	M. Hugher.
	Wayne P. Mughes Jr., Second Reader
www.chamaday.de	Peter Purdue, Chairman, Department of Operations Research
Malleman, or Magazinell, or Ma	Knight. Mamkell
	Kneale T. Marshall Dean of Information and Policy Sciences

ABSTRACT

This thesis explores the use of two analytical methods for obtaining a priority ranking of selected Advanced Base Functional Components (ABFCs) with regard to relative importance to mission accomplishment during the early days of a general wartime scenario. Specifically, eleven of the ABFCs most frequently mentioned by the Fleet Commanders-in-Chief as being their most urgent requirements were rated in two survey formats, one using categorical judgments and the other using a method of paired comparisons. In examining the results of using these methods, this study: 1) provides one-time relative rankings of the ABFCs that were compared, 2) describes the differences in scope and application of the two techniques, and 3) provides a foundation for further study to obtain meaningful quantitative measurements of the need for selected ABFCs, measurements which can be used as aids to decision making in the budgetary process.






TABLE OF CONTENTS

I.	INT	RODUCTION 1
П.	NAT	TURE OF THE PROBLEM
III.	PRO	OCEDURE 5
	A.	SELECTION OF THE MODELS
	B.	CONSTRUCTING INTERVAL SCALES FROM CATEGORICAL
		JUDGMENTS 6
	C.	THE CONSTANT SUM METHOD
	D.	THE ANALYTICAL HIERARCHY PROCESS
	E.	SELECTION OF JUDGES
	F.	THE SURVEYS15
		1. Survey 1: Categorical Judgments
		2. Survey 2: Pairwise Comparisons
	G.	ANALYSIS
		1. Transformation of Survey 1 to Scale Values
		2. Transformation of Survey 2 to Scale Values using Both the
		Constant Sum Method and the Analytical Hierarchy Process 17
IV.	RES	ULTS 19
	A.	CONSTRUCTING INTERVAL SCALES FROM CATEGORICAL
		JUDGMENTS19
	В.	THE CONSTANT SUM METHOD USING PAIRWISE
		COMPARISONS 19
	C.	THE ANALYTICAL HIERARCHY PROCESS USING PAIRWISE
		COMPARISONS
	D.	DISCUSSION
V,	CON	ICLUSIONS AND RECOMMENDATIONS24

APPENDIX A.	LIST OF ABFCs STUDIED AND DESCRIPTIONS	27
APPENDIX B.	SAMPLE SURVEY PACKAGE	82
AF NDIX C.	PROGRAMS DEVELOPED FOR THESIS	91
APPENDIX D.	STEP-BY-STEP APPLICATIONS	96
APPENDIX E.	JUDGES' COMMENTS FROM SURVEYS	103
LIST OF REFE	ERENCES	107
INITIAL DISTR	UBUTION LIST	108

LIST OF FIGURES

FIGURE 1	1.	Conversion of Raw Data to Scale Values	18
FIGURE 2	2.	Scale Obtained using Categorical Judgments	19
FIGURE 3	3.	Scale Obtained using Constant Sum Method	20
FIGURE 4	1 .	Scale Obtained using Analytical Hierarchy Process	21

I. INTRODUCTION

Preparation for war is considered a most effective deterrent to war. In accordance with this philosophy, the United States has always sought to improve its ability to wage war by developing the tactics and procuring the weapons and material that will be most successful if it becomes necessary to wage, and win, a future war. Advanced bases are an important part of the preparation for war, and essential elements in the establishment of an advanced base are known as Advanced Base Functional Components (ABFCs).

The Table of Advanced Base Functional Components, OPNAV Publication 41P3b [Ref. 1] defines an ABFC as

a grouping of personnel, facilities, equipment, and material designed to perform a specific function or accomplish a mission of an advance base. [Ref. 1: p.1]

There are currently over 200 identified ABFCs, arranged in categories by type, including such types as administrative, medical, and communication-related ABFCs.

OPNAV Publication 41P3B is a catalogue of all formally designated ABFCs, and describes each one in terms of its intended mission, personnel required, cost data for preliminary planning, and material handling data for use in transportation planning. These data are used for the planning and procurement of ABFCs so that operations plans (OPIANS) and concept plans (CONPIANS) can be immediately and successfully executed in individual theaters in the event of a contingency. Thus, ABFCs comprise a substantial budgetary requirement in the business of preparing for war and other actions in defense of the United States and its allies.

The current procedure in the Department of the Navy is to plan ABFCs as War Reserve Material for future contingencies, rather than attempt to assemble them at time of ramp-up. This reduces the risk of ha ing insufficient time to obtain the various materials that comprise ABFCs needed by the Fleet Commanders-in-Chief (FLTCINCs) in the most crucial early stage of the conflict.

II. NATURE OF THE PROPLEM

As is the case with most logistics items in the planning system, ABFCs are not in a ligh priority category for budgeting purposes. The resources that will be needed in the near term, e.g., permanent-change-of-station (PCS) funds, servicemember pay and allowances, and weapons designed to meet a projected threat, always take precedence in the competiton for limited defense funds. In the currently austere climate of government spending, it is especially difficult to obtain funds for non-urgent logistic support materials such as ABFCs. The problem then, for defense planners and ABFC sponsors, is to convince those who apportion the budget of the importance of ABFCs to the successful accomplishment of the FLTCINCs' and the Navy's mission: to be prepared for, and thus, to deter war.

Much of the difficulty in obtaining fulls for ABFCs has been attributed to the fact that the need has been qualitatively, rather than quantitatively identified. It is easier to justify defense spending on an item or program when a numerical operational value is associated with it. If the need for ABFCs could be quantified in objective terms, with the nebulous property referred to as "contribution to mission accomplishment" actually measured. ABFCs would be in a better position to obtain available funding.

The existence of different OPLANS for various conflict scenarios has contributed to the difficulty in determining such measurements. Some of the questions that arise are:

- 1. Which OPLAN should be budgeted?
- 2. Which FLTCING's requirements are the most urgent?
- 3. How should all FITCINGs requirements be combined to arrive a the proper mix of ABFCs for he bestor he the budget request?

The diversity of form and function among different ABFCs, along with the variety of conditions under which they would be employed, suggested the need for an analytical approach which could compare items that have complex and unrelated functions, but contribute to the same overall objective. The way to accomplish such a quantification is by an analysis of the marginal increase in effectiveness for each ABFC, of which this study is the first step. This research does not provide values of marginal increase in effectiveness, which is the ultimate goal, nor does it address minimum quantities of ABFCs needed for a successful mission. However, it does provide the basis from which further study can produce those values by exploring the rank ordering of individual ABFCs using scientific methods so as to identify the ABFCs most crucial to the execution of a specific operation plan.

Some methods that the author considered for solving this problem involved non-linear regression techniques, successive intervals, pairwise comparisons, and fractional factorial experiments. The particular model chosen for this study was based on the type and scope of the data that could be collected in a reasonable amount of time.

III. PROCEDURE

A. SELECTION OF THE MODELS

When ABFCs were previously used in World War II and the Vietnam conflict, the crucial activities of warfighting precluded exhaustive recording of data regarding the uses and relative benefits of ABFCs. Additionally, in peacetime, the emphasis on wartime ABFC requirements and objectives was naturally reduced. It was only recently (the early 1980's) that renewed interest was generated with regard to logistical support planning and ABFCs. [Ref. 2]

The only data previously available for use in prioritizing ABFCs was in the form of ordinal lists. These were the lists of the top thirty ABFC requirements of each Navy Service Component Commander submitted annually in June, in response to a directive of the Chief of Naval Operations. [Ref. 2] When OP-04, the assessment sponsor for ABFCs, wanted in identify the top five most critical ABFCs for the Strategic Logistics Appraisal to the Program Objectives Memorandium (POM) for 1990, the most recent of those FLTCINCs' lists were used. Taking the top thirty ABFCs listed by each FLTCINC for the current year, the overall prioritization for POM 1990 was determined by combining the professional judgments of the LLTCINCs, the ABFC resource sponsors, and the staff officers responsible for ABFC planning. For this study, the author used the eleven ABFC types most frequently mentioned by FLTCINCs in their June 1987 reports.

To solve the problem of prioritizing the need for ABFCs, it was decided that the data to be analyzed would best be obtained from the responses of

subject matter experts to a survey. Two models for obtaining relative rankings, using categorical judgments and pairwise comparisons, lent themselves readily to a questionnaire format, and were therefore chosen for this study. The analytical methods of constructing interval scales from categorical judgments [Ref. 3] and two pairwise comparison methods, the Constant Sum Method [Ref. 4] and the Analytical Hierarchy Process [Ref. 5], were chosen for manipulation of the data because of their direct applicability to the models and their ease of use.

B. CONSTRUCTING INTERVAL SC. LES FROM CATEGORICAL JUDGMENTS

This method employs the results of a survey which requests judges to select the category that they think best describes the item under consideration. The categories represent successive intervals on a scale of measurement of the property being studied. These categories are assumed to be mutually exclusive and collectively exhaustive on a continuum describing the property. Section F.1. and Appendix D list the categories used in this study.

This technique assumes normality of responses over the intervals and is frequently used to elicit descriptive responses from judges to obtain numerical values for a property which is difficult to directly quantify. It is discussed in a paper by Professor Glenn Lindsay [Ref. 3], and was used in a recent Naval Postgraduate School thesis to measure the relative contribution of certain factors to combat power, a study similar in purpose but different in scope and background to this one. [Ref. 6]

The mathematical procedure used to establish an interval scale from categorical judgments is thoroughly and clearly described, with examples, in

both the referenced thesis [Ref. 6: pp. 10-19] and Professor Lindsay's paper [Ref. 3]. The following is a brief outline of the steps involved in this procedure.

- 1. The raw frequencies are arranged in an array where the rows are items rated and the columns are, from left to right, the least to the most favorable categories.
- 2. The relative cumulative frequencies are computed for each row, and are placed in a new array. All values less than 0.02 and greater than 0.98 are discarded. With k the number of columns removed, and n the number of rows, m the number of columns, the array is an n x (m-k) matrix.
- 3. Using the assumption that the frequencies of step 2 are from a normal distribution, the values of Z that correspond to them are obtained from a standard normal distribution table. These are placed in a new array.
- 4. The row average, \overline{z}_i is computed for each row (item) in the array obtained from step 3.
- 5. The column average, \overline{b}_j , is computed for each column in the same array. These values are the upper bounds on the categories represented by each column for the scale being developed.
- 6. The grand average of all values in the array, $\overline{\mathbf{b}}$, is computed.
- 7. The sum of squares of the differences between the grand average, $\overline{\mathbf{b}}$, and the column averages, $\overline{\mathbf{b}}$, is computed. This result may be referred to as B.
- 8. The sum of squares of the differences between the normalized row averages $\overline{z_i}$ (from step 4) and the individual normalized array values z_{ij} (from step 3) is computed for each row. The results may be referred to as A.
- 9. The square root of the ratio of B to A_i is computed for each row. The resulting values are estimates of the standard deviation from the mean of the responses for each item (row).
- 10. The scale values, S_i , for each item (row) are obtained by subtracting the product of each normalized row average, $\overline{z_i}$, and the standard deviation estimate $\sqrt{B/A_i}$, from the grand average, **b**. [Ref. 6: pp. 12-13]

The reasoning which underlies the procedure described above is as follows. Each judge has an opinion about the scale value of an item i, and this opinion is assumed to be a normally distributed random variable with

mean S_i and variance σ_i^2 . Further, a judge views the continuum of these scale values to be divisible into successive intervals (categories), and he/she also has an opinion about the location of the upper bound of each category. The judge's "feelings" about the upper bound of category j is also assumed to be a normal random variable with mean b_j and variance v_j^2 , which is the same for all category bounds, so that $v_j^2 = c$.

It follows that a judge's feelings about the distance between a category's upper bound and the scale value of an item will also be a normally distributed random variable with mean $b_j' - S_i^*$ and variance $\sigma_i^2 + c - 2\rho_{ij}\sigma_{ij}$. It is assumed that the correlation coefficient, ρ , for all pairs i and j is zero, and therefore the variance is $\sigma_i^2 + c$.

The probability that an item i is rated below a category bound j is equal to the probability that a judge's "feeling" about the distance between category j's upper bound and item i's value is that it is greater than zero. This probability can easily be converted to a probability in the standard normal distribution by subtracting the judge's mean $(b_j' - S_i')$ from the standard normal mean (0) and dividing by the judge's standard deviation $(\sqrt{\sigma_i^2 + c})$. The proportion of judges who rated item i below the upper bound of category j is an estimate of this standard normal probability. (The conversion of the sample proportion values to standard normal values is described in steps 2 and 3 above.) With these standard normal values, multiple equations are available which can be solved to obtain the scale values S_i' .

The aforementioned equations are complex to solve initially because estimates of b_j and S_i are needed, as well as variance estimates. However, this can be remedied because the item scale values and the category bounds will be eventually located on the same interval scale, providing two degrees of

$$Z_{ij} = (b_i^2 + S_i^2) / \sqrt{\sigma_i^2 + c}$$
 S_i. (Ref. 3: pp. 6-13)

C. THE CONSTANT STANDETHOD

The Constant Sum W nod employs data from pairwise comparisons in ive ranking of items of interest, with regard to order to determine the their possession of a mon property or contribution to a particular function. Respondees (fter referred to as judges) are asked to consider n elements in pairs with ...gard to a certain common property. All possible pairs are presented for consideration, for a total of (n(n-1))/2 pairs. Therefore, the Constant Sum Method is best applied to a relatively small number of elements, generally less than 15. More comparisons than this would result in a survey too lengthy for judges to complete. In accordance with this limitation, it wis decided to compare only the eleven ABFC types most frequently mentioned in the FLTCINCs' lists of to 30 requirements submitted in June 1987. A list of the ABFCs chosen and their descriptions from the Table of ABFCs [Ref. 1] are at Appendix A.

To use the Constant Sum Method as it is described in Professor Lindsay's paper [Ref. 4], the judges are asked to split 100 points between each pair, awarding the greater amount to that element which, in their estimation, possesses the greater amount of the property described. For purposes of this

study, it was decided that a point range smaller than the 100 point range would be more appropriate for comparing ABFCs, because of the diversity of their functions and to make it easier for the judges to award points. Therefore, the range of possible point values used was changed from 0 to 100 to 1 to 9, the same range of values employed in the Analytical Hierarchy Process [Re 5], which is also used in the State of the Art Contingency Anasis (SOTACA) model created for planners in the Office of the Joint Chiefs of Staff. [Ref. 7: pp. 4-27] This range was considered the best, based on previous study and Saaty's assessment:

Experience has confirmed that a scale of nine units is reasonable and reflects the degree to which we can discriminate the intensity of relationships between elements. [Ref. 8: p. 77]

The following is a list of the point values (hereafter referred to as intensity values) and their descriptions, as modified for the ABFC survey:

INTENSITY VALUE	DEFINITION	EXPLANATION
1	Equal importance	Loss of these two ABFCs would cause <u>equal</u> detriment to the mission. Both are needed equally.
3	Weak importance of one over the other	Your experience and judgment tell you that one ABFC is moderately needed more than the other.
5	Essential or strong importance	Experience and judgment tell you that one ABFC is strongly needed more than the other.
7	Very strong importance	One ABFC is <u>very strongly</u> <u>needed</u> more than the other; its dominance is obvious from experience.

9	Absolute importance	Your unqualified opinion is that there is the <u>highest</u> order of need for one ABFC over the other.
2 , 4 , 6 , 8	Intermediate values between two adjacent intensities	When you must compromise. [Ref. 5: p. 54]

These intensity values were converted to a 100 point scale for employment in the Constant Sum Method by performing a ratio transformation, as follows:

of points awarded to = (intensity value x 100) \div (intensity value + 1) preferred component

of points awarded to = 100 - the above result other component in pair

This transformation results in a 100 point split which is equivalent to the intensity value. Therefore, an intensity value of 1, which indicated equal importance, was translated into a 50 - 50 split between the pair.

Each judge's responses on the 100 point scale are then assigned to an n x n matrix, with a_{ij} being the number of points awarded to component j when compared to component i, and a_{ji} being the number of points awarded to component i in that same comparison. There is one matrix for each judge, and cross-diagonal elements in each matrix sum to 100, with all diagonal positions containing the value 50.

Taking an average of all elements over a total of m judges, one composite matrix is formed, called AB, where

$$\frac{\sum_{k=1}^{m} a_{ijk}}{a_{ij}} = \frac{k=1}{m}$$
 (k denotes judge). (1)

This aggregation of the judges' responses is used for all remaining calculations, so that the number of judges is hereafter suppressed. This implies that this method can be used with the responses of <u>any</u> number of judges, although a large number (>20) would provide a less biased result for use as a group decision aid.

A new n x n matrix, called W, is computed from the AB matrix as follows:

$$W_{ij} = \frac{\overline{a}_{ij}}{\overline{a}_{ji}}$$
 (2)

where cross-diagonal elements in the W matrix are reciprocals of each other. The ratio of $\overline{a_{ij}}$ to $\overline{a_{ji}}$ is an estimate of the ratio of the scale value of item j to the scale value of item i. Therefore, from equation (2):

$$W_{ii} = \text{estimate of } S_i / S_i$$
 (3)

where S_i is the scale value for component i. Assuming that this estimate is a perfect estimate for S_j / S_i , we can take natural logarithms of the equality. The result is

$$\ln W_{ij} - (\ln S_i - \ln S_j) = 0.$$
 (4)

If n, the number of components analyzed, is greater than three, there will be more estimating equations than there are scale values to estimate. The method of least squares is employed to resolve this problem. The difference between the W value (the estimate of the ratio of the scale values) and the true ratio of the scale values is minimized using the derivative of the natural logarithm form of equation (4). The steps below show how the least squares method is used.

Scale values are sought which satisfy the following:

minimize X, where

$$X = \sum_{i=1}^{n} \sum_{i=1}^{n} \{\ln W_{i_i} - (\ln S_i - \ln S_i)\},$$
 (5)

Taking the derivative of equation (5) with respect to S, setting $\delta X / \delta S = 0$, and solving for $\ln S$, results in

$$\ln S_{j} = \frac{\sum_{i=1}^{n} \ln W_{ij}}{\sum_{i=1}^{n} \ln S_{i}} = \frac{\sum_{i=1}^{n} \ln S_{i}}{\sum_{i=1}^{n} \ln S_{i}}$$

$$= \frac{\sum_{i=1}^{n} \ln W_{ij}}{\sum_{i=1}^{n} \ln S_{i}} = \frac{j=1,2,...,n}{n}.$$
(6)

Any unit of measure can be chosen for the scale, which is unitless.

Therefore, to simplify the computations, set the mean scale value to zero:

$$\sum_{i=1}^{n} \ln S_{i}$$

$$\vdots = 0.$$
(7)

Substituting the result of equation (7) into equation (6), the least squares estimates of the scale values become

$$\ln S_{j} = \sum_{i=1}^{n} \ln W_{ij}$$
 $j=1,2,...,n$. (8)

Solving for individual S's shows that each scale value is equal to the geometric mean of the values of the corresponding column in the W matrix, or

$$S_{j} = \begin{bmatrix} n \\ \pi \\ i=1 \end{bmatrix} (W_{ij})$$
 $j=1,2,...,n$. (9)

[Ref. 4: pp. 3-4]

D. THE ANALYTICAL HIERARCHY PROCESS

The Analytical Hierarchy Process of computing scale values from pairwise comparisons employs the same 1 to 9 scale of preference intensity values described in Section III. C. above. However, the mathematical method varies somewhat. If a judge awards an intensity value of 5 to item X when

preferring it to item Y, then it is assumed that the converse comparison, the value of preference of item Y "over" item X is the reciprocal, or 1/5. Therefore, the missing values in the raw data matrix, i.e., the positions that are cross-diagonal to the whole number comparisons that the judges provided, would be the reciprocals of those whole number values. [Ref. 5: p. 78]

Using the whole number values provided by judges as the raw data, the steps in the method are outlined below.

- 1. Construct the completed matrix for each judge by inserting the appropriate reciprocal values in the blank cross-diagonal positions, and enter the unit comparison (1) down the main diagonal. These matrices will be referred to as the A-prime matrices, with the entries a'u.
- 2. To aggregate the responses of all judges, take the geometric mean of the corresponding a'_{ij} values. The result is a single matrix, which can be called the AB-prime matrix.
- 3. Normalize the resulting matrix by dividing the column elements, a'_{ij} , by the respective column sums, $n \sum_{i=1}^{n} a'_{ij}$
- 4. The scale values, S_i, are computed by averaging over the normalized columns obtained from step 3 above. [Ref. 5: pp. 19-20]

E. SELECTION OF JUDGES

Because of the need for subject matter experts in ABFC and/or logistical planning, judges for this study were individually selected. They were obtained by accessing three sources. Persons who attended the Workshop in Operational Logistics at the Naval Postgraduate School, Monterey, California, in February, 1987 were considered to be candidates, and those who were assigned to staff positions involving logistics planning outside the Naval Postgraduate School were selected to serve as judges. The planning sponsor for ABFCs in OP-41, CDR Bob Miller, and other members of the OP-04 staff provided the names of staff members in various commands with whom they

worked on matters involving ABFC definition and planning, and they were added to the list of judges. Finally, judges were asked in the survey itself to make copies of the survey and forward them to other individuals who were familiar with some or all of the ABFCs.

F. THE SURVEYS

A total of 24 judges were selected to participate, and a package containing both surveys (the one requesting categorical judgments and the one requesting pairwise comparisons) was forwarded by mail to each one. sample survey package is at Appendix B. The scenario described for use by the judges in framing their responses to both surveys was associated with the most general of the OPLANS, and is known as the "base case" scenario. In general, this scenario is the outbreak of global conventional war, with the fighting starting in Europe. It was deemed appropriate to use the "base case" scenario because it is familiar to fleet planners, is the most mature of the OPLANS, and as the description suggests, is considered widely applicable. In addition, the "base case" scenario was adopted because of the accessibility of the background information (individual OPLANS are classified) and because of the ability to locate, in a short time, a sufficient number of subject matter experts familiar with the general plan. This generalization of the situation was also the most appropriate to use because of the initial goal: to prioritize ABFC types by contribution to mission accomplishment, without determining which is the most crucial theater or which OPLAN is most likely to be executed in the next contingency. Finally, staff members in the ABFC planning arena who were queried recommended the "base case" scenario as the best one to be used for the purposes of the survey.

1. Survey 1: Categorical Judgments

By stating that the judge had all the ABFC assets he/she needed, and by requesting a rating of detriment to the mission if a given ABFC capability was lost, it was possible to elicit the importance of each in its own right, unaffected by the others. There were four categories to describe the detriment felt if the capability of the given ABFC was lost: no detriment, some detriment, serious detriment, and warstopping. These were chosen because they seemed to be mutually exclusive and collectively exhaustive in describing possible levels of detriment.

2. Survey 2: Pairwise Comparisons

For the pairwise comparison survey it was decided that the best way to elicit a judge's estimate of the importance of a given ABFC to warfighting capability, relative to other ABFCs, would be to phrase the survey as follows: If all ABFCs were initially available, and both of those in the given pair became unavailable, which loss would cause the most detriment to warfighting operations? In addition, how much more intense would be the loss of it than the loss of the other?

It was determined that the positions of the pairs on the survey should be random, so as to preclude a response from being dependent on another response involving a nearby pair with a common component. To randomize the positions, each pair was assigned a number from 1 to 55, and the number 55 was operated on using the monadic function "roll" in APL (A Programming Language). The command "roll n" causes the program to select each of the integers from 1 to 55 in random order, until all possible integers in that range have been chosen. The vector produced by the command "roll 55" was the order in which the pairs were placed in the survey.

G. ANALYSIS

1. Transformation of Survey 1 to Scale Values

A total of 23 completed surveys were received for analysis, and the responses were manually tallied and entered into an array in APL (A Programming Language). Eleven ABFCs were rated, and with the four categories, the input was an 11 x 4 matrix. Three APL programs created by Paul Crawford [Ref. 6. pp. 87-88] to perform the computations of this technique were reviewed, and it was determined that they were general enough to be applied to the data in this study. These programs included: Normalization of Camulative Frequencies, Normalization of Camulative Frequencies. The programs are included at Appendix C. The process of converting from the raw data of Survey 1 to scale values is recreated in Figure 1. The data obtained using this process are included at Appendix D.

2. Transformation of Survey 2 to Scale Values using Both the Constant Sum Method and the Analytical Hierarchy Process

The 23 sets of responses to the paired comparison survey were entered into a computer data file that could be read by a FORTRAN computer program. A FORTRAN-77 program was created which performed all calculations necessary for converting the raw responses (intensity values) into scale values for each of the ABFCs using both analytical methods. This program is at Appendix C. Both methods of converting the raw data from survey 2 into scale values are shown in Figure 1. The data obtained using the two processes are included at Appendix D.




Figure 1. Conversion of Raw Data to Scale Values

IV. RESULTS

A. CONSTRUCTING INTERVAL SCALES FROM CATEGORICAL JUDGMENTS

The final scale positions obtained from this procedure for each ABFC studied are shown in Figure 2.




Figure 2. Scale Obtained using Categorical Judgments

B. THE CONSTANT SUM METHOD USING PAIRWISE COMPARISONS

The final scale positions of the ABFCs obtained from this precedure are shown in Figure 3.




Figure 3. Scale Obtained using Constant Sum Method

C. THE ANALYTICAL HIERARCHY PROCESS USING PAIRWISE COMPARISONS

The final scale positions of the ABFCs obtained from this procedure are shown in Figure 4.

D. DISCUSSION

The rankings obtained using the method of constructing interval scales from categorical judgments show the importance of individual ABFCs, without regard to the preference of one of them over any other. This is perhaps the purest scale for measuring the contribution to mission accomplishment of any given ABFC.

With regard to the two mathematical techniques used on the data obtained from patrwise comparisons (the Constant Sum Method and the




Figure 4. Scale Obtained using Analytical Hierarchy Process

Analytical Hierarchy Process), the numerical scale values obtained for the ABFCs are different, but the rank orderings of the ABFCs are identical (see Figures 3 and 4). This feature was expected, in view of the fact that the two methods are equivalent in rationale and use the same raw data. The final rankings seemed to match the intuitive predictions made by the author after review of the raw responses from the completed surveys before they were entered into the program. For example, it was noticed that the medical type ABFCs were frequently disfavored when compared to any of the other types, and they are the last two in the rank ordering. Also, many judges consistently favored the Rapid Runway Repair Kit and the Cargo Handling Battalion over other types, and they were computed to be the top two in the list.

The aforementioned rankings obtained from the pairwise comparison data are different from those obtained from the categorical judgments (using the interval scale technique) (Figures 2 and 3). These differences can be attributed to the introduction of dominance in the process of making pairwise comparisons. For example, the need for a Blood Bank in its own right is validated strongly by the responses to Survey 1, but when it is always being compared to another, usually an "attack-oriented" ABFC, where one of the pair can be chosen to be more important, it is consistently dominated. This helps to explain its position at the bottom of the relative ranking in the Constant Sum Method and Analytical Hierarchy Process.

Despite an overall difference in the rankings, the number one and number two ABFCs resulting from the pairwise comparisons and the categorical judgments were the same: Rapid Runway Repair and Cargo Handling Battaiton, respectively. This validates the strength of the judges' views on their importance to the mission, both in their own right and when compared to other ABFCs. Similarly, Casualty Staging Unit and Blood Bank remained the last two in the rankings obtained from both methods. This high correlation between the results of two very different methods of ranking emphasizes that warfighting mission ABFC types (e.g., Rapid Runway Repair, etc.) are of much greater importance to the judges than life support types (e.g., Casualty Staging Unit, Blood Bank). This could be the result of a strictly operational and combat orientation of most of the judges polled as well as the fact that the scenario was stated to be the very earl, days of the conflict when casualties can be assumed to be low. If the author had been able to poll more individuals with different personal orientations, the responses and results may have been different

The same of the same

The differences in rankings produced by the categorical judgments as opposed to the pairwise comparisons occurred among the middle rankings (Figure 2 versus Figure 3 or Figure 4). Two computations were performed to measure the significance of those differences. The Rank Coefficient and Spearman's ρ are two measures of rank correlation which both have a possible range of -1 to 1. A value of -1 represents perfect disagreement between the rankings, while a value of 1 represents perfect agreement. For the two methods used in this study, the Rank Coefficient computed was 0.70709 and Spearman's ρ was 0.97121, indicating strong agreement between the methods.

V. CONCLUSIONS AND RECOMMENDATIONS

Although individual measures of effectiveness for ABFCs were not obtained, the models used in this study provided relative measures of the contribution of each one to mission accomplishment. The model used in Survey 1, categorical judgments, made no assumptions about the relationship of one ABFC to another, but placed each one in its estimated position on a common scale. The method of paired comparisons used in Survey 2 provided the same kind of result, but required that judgments be made on a ratio scale, implicitly assuming a common origin for the ratio.

The three analytical procedures (construction of the interval scale, the Constant Sum Method, and the Analytical Hierarchy Process) are computationally simple and were easily performed using the data from the surveys. They are useful tools for converting judges' opinions to relative quantities. In particular, the Constant Sum Method and the Analytical Hierarchy Process are simple, yet effective models for obtaining scale values for diverse components when a ratio scale is desired or acceptable. However, the fact that all possible pairs must be considered makes them too cumbersome for surveys to be used if the number of components to be compared is larger than 15.

Based on the assumptions made for Survey 1 using categorical judgments (normality, homogeneity of variance), the interval scale values obtained give the following information: of the eleven ABFCs rated, Rapid Runway Repair is most needed for mission accomplishment, Cargo Handling Battalion is next most needed, etc. Only relative rankings are obtained, and no statements can

be made about proportionality of values, etc. However, one can make the statement that, if it is determined that the Blood Bank is essential to the mission, then the AMCC Van is more essential, and the Rapid Runway Repair is much more essential. No other statistical conclusions can be inferred.

In Survey 2, no underlying assumptions were made about normality, as in Survey 1. However, a common origin for the 1 to 9 scale of intensity values was assumed, and relative rankings were derived from the results obtained using the two techniques for pairwise comparisons (Constant Sum Method and Analytical Hierarchy Process). In addition, because the resulting values were on a ratio scale, one can say that Cargo Handling Battalion is needed approximately twice as much as High Speed Fuel Dispensing System. Distances between items on the scale can be commented on in terms of proportionality.

For purposes of choosing between two ABFCs with regard to need, it is intuitively felt that the Constant Sum Method would be more useful as an aid to decision-making involving preference. However, the method of constructing interval scales from categorical judgments is more trustworthy because the judges are given descriptive reference points to bound their ratings, and assumptions of normality and homogeneity of variance are appropriate. Therefore, the rank ordering of ABFCs obtained from the categorical judgments of Survey 1 is considered to better reflect the true hierarchy in terms of contribution to mission accomplishment. It is interesting to note that when solicited for comments regarding which survey was more appropriate for the purpose described, judges frequently mentioned that Survey 1 was better because it was easier to respond to. Appendix E contains a synopsis of those comments.

Further study is recommended to determine the minimum amounts of a given ABFC needed for the success of both the 'base case' and other particular OPLANS. Also, cost effectiveness could be examined. It was not considered in this study and the notion arose that, if judges had been specifically requested to consider the costs of the different ABFC packages (including purchase and transportation costs), the responses might have been different. Future research should include the cost consideration, while asking judges whether they preferred, for example, two Blood Banks or one Aviation Tank Farm.

A full factorial experiment should be performed, using categorical judgments, to determine the marginal increase in mission effectiveness for each crucial ABFC type. Also, a similar experiment which compares different ABFCs not only to each other but also to such items as weapons, spare/repair parts, fuel, etc. would be especially useful to support decisions involving trace-offs in the budget. The results would provide a valuable decision aid for planners and sponsors in making appropriate budgetary decisions, as well as justifying them, in the future.

APPENDIX A. LIST OF ABFCS STUDIED AND DESCRIPTIONS

LIST OF ABFCs

- 1 Naval Station Communication (AMCC Van)
- 2 Cargo Handling Battalion
- 3 P-3C Intermediate Support Facility
- 4 Tank Farm (medium, DFM & JP-5)
- 5 Rapid Runway Repair
- 6 High Speed Fuel Dispensing System
- 7 Casualty Staging Unit
- 8 P-3A/B Intermediate Support Facility
- 9 Flood Bank
- 10 Aviation Tank Farm (basic)
- 11 Naval Overseas Air Cargo Terminal (large)

The following pages contain descriptions from the Table of ABFCs [Ref. 1] for the ABFCs listed above, including mission, equipment, personnel, and supplies needed. 1. MISSION - A transportable communications component to provide local and long haul, external communications to support a small naval station or naval air facility including common user access to the Naval Communications System. Specialized subsystems for local air/ground, GCA, industrial, security, port services, etc. are not included. (The C3A component is selfsufficient. No other ABFC components are required for its operation. The C3A component is capable of supporting any ABFC components that require communications support.)

The Advanced Base Functional Component (ABFC) C3A van contains the following systems/circuits in one transportable equipment shelter with two portable generators:

- a. One secure voice circuit via satellite (FLTSEVOCOM).
- b. Two wideband secure voice circuits via UHF Line of Sight (LOS) (NESTOR).
- c. Two narrowband secure voice circuits via URF LOS, UHF Satellite, HF, or landline (PARKHILL).
- d. Two full duplex secure teletype (TTY) circuits each capable of UHF LOS, UHF Satellite, HF, or landline operation.
 - e. One UHF satellite AN/SSR-1 receive broadcast circuit (FLTSATCOM).
 - f. Two HF plain voice circuits (HICOM).
 - g. Two UHF LOS plain voice circuits.

The ABFC van is an insulated aluminum shelter mounted on a mobilizer which may be transported by air, ship, or towed by a prime mover. The van is designed to be transportable via (a single lift in C-130 or larger aircraft or the CH-53E helicopter (with lifting slings)). The van is capable of being towed at speeds up to 50 MPH on smooth terrain or speeds up to 25 MPH on rough terrain. Primary AC power for the van is normally provided by a 30 KW portable generator (two are provided). The van also has the capability to utilize power sources other than the generator, such as base or commercial power. (The ABFC (C3A) van system is 100 percent containerizable.)

The total ABFC van system consists of the following components:

- a. ABFC (C3A) Shelter, Gichner Model GMS-240-MF-(ISO)
- b. MEP-005 30 KW 50/60 Hz Generator (2 each) with the following modifications: fuel winterizing kit, electric winterizing kit, wheel mounting kit, and spark arrestor kit.
 - c. M-1022 Mobilizers and Adapters
 - d. Major/Ancillary/Electronics Equipment

- e. Test Equipment
- f. 35' Whip HF Transmit Antennas (two each)
- g. Redical Satellite Antenna
- h. TACO D-2214 Omnidirectional UHF Antenna
- 1. 35' Whip HF Receive Antennas (two each).
- j. AS-2815/SSR-1 Satellite Receive Antenna

0 OFFICERS

- k. Power Distribution/Monitor/Protection System Part of (P/O) Shelter
- 1. Interconnecting Cables

2. PERSONNEL

			OFFICERS		ENLISTED MEN				STED 1	MEN -
Ech	No	Rank	Desig	Billet	Rate	Gp	Pa; Gr	-	SNEC	Title
	1				RMC	5	7	2319		Technical Controller Supervisor
	1				ETI	3	5			ABFC (C3A) Meintenance Technician
	1				ET13		6			SATCOM Technician
	1				EN2	7	5			Refrigeration/AC Technician
	1				EM2	7	5	5632		Shore Based Fower Technician
				Enlist	ed Mer	ı (Au	gnen	noitation	Crew)	
	2				RM2	5	5	2318		Technical Controller-Operator
	1				RM3	5	4	2318		Technical Controller-Operator
	1				PJ:12	5	5	2.316		TIY Repair
	1				ET2	3	5	1420		HF Transmitter Technicien
	1				ET2	3	5	1445		KY 75 Technician
	1				ET2	3	5	1425		WSC-3 Technician
	1				ET2	3	.5 A	T6632		KY 28 Technician
	1				EM3	7	4	5632		Shore Based Power Technician
	1				EN3	7	4	4294		Refrigeration/AC Technician
	1				SK3	5	4			Supply Clerk (Independent Duty)
	1				HNI	10	દ			Corpsman (Independent Dury)

17 ENLISTED HEN

TOTAL 17

Enlisted Men (Security Force-if required)

POI 6 Leading Party Officer (Security)
SN/SA 1/2 Small Arms Trained (Security)

3. COST

NAVAIR

SPAWAR The cost for SPAWAR managed items \$2,000,000

NAVFAC \$123,228

NAVSUP

NSF

NAVFAC

Identified (Other) \$ 4,743

4. CONSTRUCTION

Cleared 600 foot diameter area

Power: 1 KVA

Construction Time: 200 Man hours

5. MATERIAL (MAJOR ITEMS)

1 EA Communication shelter

2 EA 30 KW generators, trailer mounted

1 EA Truck, 2 1/2 ton, 6x6 not P/O Communications van

2 EA Trucks, 3/4 ton, 4x4 not P/O Communications van

Supplies

Installation material and tools Administrative and general supplies Fuel and POL Spare parts Same as COSAL 005 885.

Facilities (Required but not included)

Personnel housing and support Telephone hook up service Storage for spares

WEIGHT: 43,300 lbs (21.7 Short Tone)

CUBE: 3500 CU. FT. (87.5 Measurement Tons)

NAVAL SUPPLY SYSTEMS COMMAND

Sub-Function Codes

Ref		WI	CU
11 Administrat	1536	135	
14 General equ	ipment and supplies	436	44
	SPACE AND NAVAL WARFARE SYSTEMS COMMAN	ND	
	MAJOR EQUIPMENT		
DESCRIPTION	N	U/I	QTY
TSEC/KY-58	Crypto	EA	2
*TSEC/KY-28	Crypto	£A.	2
**Duel PARKHILL	. Crypto	EA	1
**TSEC/KG-36	Crypto	EA	2
**TSEC/KW-7	Crypto	EA	4
**TSEC/KWX-11	Crypto	E.A	4
AN/WSC-3(V)2	UHP SATCOM and LOS Receiver	£Α	4
UHF Diplexer	SATCOM Diplexer	E.A	1
Presmplifier	SATCOM Preamplifier	L A	1
AN/URY-23	HF Transmitter .	EA	2
AN/URA/38	HF Multicoupler	EA	2
AN/SSR-1	UHF Satellite Broadcast Receiver	EA	1
AM-4823	HF Preselector	E.A	4
DA-607	Dummy Load (Part of P/O) AM-4823)	EA	1
CD-1961/D	Antenna Coupler (P/O AM-4823)	ZA	1
R-1051F/URR	HF Receiver	EA	4
AN/URA-17P	TIY Converter	FA	2

F.A

CV-3333/U Vocoder

MAJUR EQUIPMENT (CONTINUED)

		U/I	QTY
ON-143(V)4/US	Q Interconnecting Group	ЕA	1
TT-603	TTY Transmitter Distributor	E A	2
TT-605	TTY Reperforator	EA	2
AN/UGC-77	TTY Keyboard Printer	EA	4
AN/URQ-23	Frequency Standard	EA	1
AM-2123	Frequency Distribution Amplifier	EA	1
TH-83	Hubbing Repeater	E A	1
C-8657	Autophaser	EA	1
PP-6521/FG	+ or - 6 VDC Power Supply	EA	2
SB-3684/FG	Ballast Lamp Panel	F.A	2
SB-3503/FG	Fuse Panel	EA	2
SB-3092	Audio Patch Panel	EA	2
SE-3189	DC Patch Panel	EA	3
ME-400	+ or - 6 VDC Monitor Meter (P/O AM-4823)	EA	2
NONE	Dual Parkhill Speaker Assembly	EA	1
NONE	Dual Parkhill Cable Termination Assembly	EA	1
NONE	Dual Parkhill Line Termination Assembly	EA	1
NONE	AN/SSR-1 Low-Level Driver	EA	1
NONE	KY-58 Interface Adapter	EA	2
NAVAIR 19-45-2	28 VDC Power Rectifier	EA	1
Acopian Model	28 VDC Power Supply	F.A	1
Andrews 63305-5	UHF Helical SATCOM Antenna	F.A	1
CU-691/U	Antenna Coupler	EA	1
SA-2.81	RF Distribution	EA	2

MAJOR EQUIPMENT (CONTINUED)

		U/I	YTO
AS-2815/SSR-1	UHF Satellite Broadcast Receive Antenna	EA	1
D-2214	UHF Omnidirectional Antenna	EA	1
NONE	35FT HF Whip Antenna	F.A	4

^{*}NESTOR terminals (KY-8, KY-28, KY-38) are in the process of being replaced by VINSON COMSEC equipment (KY-57, KY-58). When phase-in is complete all NESTOR equipment will require one-for-one replacement by VINSON.

ANCILLARY EQUIPMENT

DESCRIPTION		U/I	QTY
Security Storage Safe		EA	1
LPW-300	TTY Faper Winder	EA	4
Tork Model 430	Emergency Lights	EA	1
Adtech 5060A	Dual Speaker Amplifier	FA	4
GTE Model 500	Telephone	FA	1
WECO Model 270BW	Automatic Disconnect Switch	EA	1
WECO Model RIAW	Non-Inductive Kinger	FA	1
H-169/U	Handset	F.A	2
TTT Model 00069-C3-13	Handset	FA	2
Locally Manufactured			
NN/SSR-1 Monitor/Patch Pa	nel	FA	1
Trusk Monitor/Patch Panel		FA	1
UHP Secure/Plata Voice Co	ntrol Panel	ΕA	1
28 VDC Control Panel		FΑ	

^{**}FARKHILLS will eventually be replaced by ANDVT in the post FY-87 time period. KG-84 equipment is replacing KW-7/KG-36 equipment in the FY-88 time period.

ANCILLARY EQUIPMENT (CONTINUED)

		U/I	QTY
AC Power Monitor	Pauel	P A	1
AC Power Phase De	EA	1	
Suppression As	saembly		
Plain Voice Ampli	lfier Assembly	EA	1
UHF Secure Voice	Red Junction Box	EA	1
UHF Secure Voice	Black Junction Box	ŁА	1
Black Main Distri	bution Frame	EA	1
Red Main Distribu	ction Frame	FA	1
Power Combiner As	sembly	EA	1
RT-1107/WSG-3 Pat	ch Panel.	EA	1
1A-970	Voice Handset	EA	8
MK-250	Antenna Pressurizing Kit	EA	1
NONE	HF Patch Panel	E4	1
NONE	Equipment Racks	E Company	15
	ANTENNA AND MISCELLANEOUS CA	LBLES	
Description		ti/I	QTY
URF Transmission	Line Cable, RF, W435	FA	1
UHF Transmission	Line Cable, Rr, W435A	EΛ	1
AS-2815/SSR-1 Tran	namission Line Cable, RF, W437	Rian's	1
HR9N-P Transmissio	on Line Cable, RF, W438	EA	1
HP Receive Whip Tr	ausmission line Cable, RF, W401	EA	ì
HP XMT Whip Transm	dission Line Cable, RF, W416	દ _્ રત્	1
HP XMT Whip Ireass	dission Line Cable, RF, W417	EA	1
SP XMT Whip Couple	r Control Cable W702	EA	1
HF XMT Whip Couple	r Control Cable W703	EA	1

ANTENNA AND MISCELLANEOUS CABLES (CONTINUED)

Generator Power Cable, AC, 4 Cond	EA	1
Generator Parallel Cable, AC, 4 Cond	EA	Ĩ
Signal Grd Cable Wire #2/0 AWG	EA	1
HY Antenna GRD Plane Wire #8AWG with 2 1/2 FT Grd Rod	EA	30
35 Ft Whip Antenna Nylon Rope Guys	FA	9
Van Lifting Sling P/C Van	E A	1

TECHNICAL DOCUMENTATION

NAME	SPAWAR NO.
Satellite Communications Set AN/W3C-3 VOL-1 VOL-2 VOL-3	0967-LP-545-4050 0967-LP-545-4060 0967-LP-545-4070
Operating Instructions Satellite Set AN/WSC-3	0967-LP-545-4020
Receiving Set. Satellite Signal AN/SSR-1 & AN/SSR-1A	0967-LP-541-9020
Antenna Coupler Group AN/URA-38A	0967-LP-297-6010
Radio Receiver R-1051 P/UER	C957-LP-617-7010
Maintenance Stundard Book Padio Receiver R-1051F/URR	· 0967-LP-617-7020
Audio Digital Converter CV-3333/U	0967-LP-617-1010
Low Level Tech Control Equipment	0967-I.P-391-6010
Interconnecting Group On-143(V) USQ	0967-LP-614-7010
Telephone Set TA-970/U	0907-LP-625-2010

TECHNICAL DOCUMENTATION (CONTINUED)

NAME	SPAWAR NO.
Transmitter - Teletypewriter Control C-8657(P)/UG	0967-423-6010
	NAVSHIPS NO.
Radio Frequency Preselector - Amplifier AM-4823/U	0967-28-3010
Antenna Coupler CU-691/U	0969-LP-969-8010
Technical Document Drawings 27732-28000	
Model 28/32 RFI Wiring Diagram Package	-
Wiring Diagram Package for Receive Only Typing Reperforator	-
Teletype Bulletin 295B Motor Unit	-
Teletype Bulletin 1197B Model 23 Compact TTY Set	0967-059-9020
Teletype Bulletin 284B Model 28 Compact TTY Set	0967-059-3010
Teletype Bulletin 284B Model 28 Compact TTY Set	0967-059-9030
bulletin 322b/RF 28 Reperferator & Tape Printer	0957-173-9030
Bulletin 322B 28 Reperforator & Tape Printer	0967-173-9020
Bulletin 322B 28 Reperforator & Tape Printer	0967-173-9010
Frequency - Time Shandard AN/URQ-23	ET710-AA-0P-1-010/5102
	NEFACTPHIL NO.
AMCC Van Installation Drawings	26990-40301

TECHNICAL DOCUMENTATION (CONTINUED)

NAME	NEEACTPHIL NO.
AMCC Van Test Plan .	26990-40218
AMCC Van Technical Manual	26990-40325
	STEWART WARNER 40.
Radio Transmitter Set AN/URT-23C(V)1	01A228010-C1
Radio Transmitter T-827H/URT	01A228010-01
Maintenance Standard Book Radio Transmitting Set AN/URT-23C(V)1	•••
	GOULD NO.
Group Signal Radio Converter AN/URA-17E	EE162-AH-OM1-710/ E110
	NAVAIR NO.
Power Supply 28 VDC Transformer Rectifier	19-45H-2
Air Conditioners/Heat Pumps	19-60-83
Air Transportable Integration Unit Mobile Pacility	19-25-173
Mobile Facilities Log Book Inventory Record	uae-
	DIGITECH NO.
Instruction Manual for Model 2002-09 Digitech Analyzer/Generator	-
	ARMY 'IM
Dolly Set, Lift, Transportable Shelter Technical Manual Package XM832	-

NAVAL SEA SYSTEMS COMMAND

TEST EQUIPMENT

Peacription .		U/I	QTY
28480-5328A-H99	Frequency Counter	EA	1
89536-8000A/BU	Digital Multimeter	EA	2
80009-2336	Oscilloscope	EA	1
70998-4410-025	FEEDTHRU Wattmeter	EA	1
28480-334A	Audio Distortion Analyzer	EA	1
Digitech Model 2002-08	TTY Test Set	EA	1
28480~3550B	Audio Test Set	EA	1
99899-477230	30dB Attenuater	EA	1
DA412/U	Dummy Load	EA	ĵ
28480-8640B-001-003	RF Signal Generator	E.A	1
TS-3228/URA-38	Test Equipment	EA	1
TS-3229/URA-38	Test Equipment	EA	1

1. MISSION

Provides personnel and facilities to process 13,500,000 pounds of air freight monthly. Processing includes palletizing, unpalletizing, handling and special treatment of hezardous cargo, distribution of in and outbound shipments by consignee, load planning, operation of ground support equipment, loading and unloading of trucks and aircraft, processing of necessary flight data and maintenance of records. This processing would be carried out on a three shifts per day, seven days per week basis. The maximum number of aircraft that can be worked at one time is three C-130s, or two C-141s or one C-5. The D29A storekeeper (SK) allowance is compatible with the mobilization allowance of two activated Naval Reserve NAVMTO Fleet Detachments.

2. PERSONNEL 5 Officers 76 Enlisted Men Total 81

		OFFICERS					ENLISTED MEN		ŒN	·
Ech	No	Rank	Desig	Billet	Rate	Gp	Pay Gr	PNEC	SNEC	Title
1	1	LT	3100	1265						FRT TRAF MGT
1	ī	LTJG	3100	1265						FRT TRAF MGT
2	1	LCDR	3100	1205						Air Traffic
2	1	LT	3100	1205						Air Traffic
3	1	LT	3100	1215						Cargo Handling
1	1				SK1	5	6			Storekeeper
1	1				YN2	5	5			Yeoman
1	2				CM2	7	5			Machinist's Mate
1	Ĺ				EOC	8	7			Equipment Operator
1	2				E01	8	6			Equipment Operator
1	5				E02	8	5			Equipment Operator
1	11				EOCN	3				Constructionman (EO)
3	3				SKC	5	7			Storekeeper
3	3				SKl	5	6			Storekeeper
3	.3				SK2	5	5			Storekeeper
3	6				SK3	5	4			Storekeeper
3	13				SN	6	3			Seaman
3	19				SA	6	2			Seaman Apprentice
3	6				E03	8	4			Equipment Operator

3. Cost

NAVAIR	
SPAWAR	
NAVFAC	\$601,493
NAVSEA	\$ 348
NAVSUP	\$756,000
NSF	\$ 53,168
NAVFAC	
Identified (Other)	\$275,445

4. CONSTRUCTION

Area required - 4.9 acres
Prefab building - 70,000 sq ft
Space requirements - Admin and Office - 1200 sq ft
Storage (covered) - 68,800 sq ft
Power required - 12KVA
Internal roads - 14,000 sq yd
Construction time - 28,591 Manhours

5. MATERIEL (MAJOR ITEMS)

Operations - 40x100 Bldgs
Materials Handling Equipment
Transportation - Trucks
Hand Tools and Consumables
Packaging Equipment and Supplies
Office Equipment and Supplies
Teletypewriters

WEIGHT: 1,284 long tons

CUBE: 2,657 measurement tons

NAVAL SUPPLY SYSTEMS COMMAND

Sub-Function Codes

Ref		WT	CU
11	Administarative Equipment and Supplies	7,552	452
14	General Equipment and Supplies	38,085	1,516
75	CO2 Transfer and Cylinder Shop	1,000	10
	Equipment and Supplies		
85	Fuel for heating	65,250	1,682
86	Fuel for vehicles and equipment under	123,766	3,236
	32 deg		
87	Fuel for vehicles and equipment over	123,316	3,225
	32 deg		
88	POL for under 32 deg	3,335	85
89	POL for over 32 deg	3,335	85
91	Materials handling equipment	666,000	34,506
	(463L MHE Provided By MAC)		
	Truck Acft Cargo A/S 32H-6,	282,060	9,600
	40,000 lbs (6eg)		

NAVAL SUPPLY SYSTEMS COMMAND (CONTINUED)

Ref	WI	CU
Trailer Pallatized Cargo A/M : (60ea)	32H-6 108,000	7,200
Truck Fork Lift A/S 32H-10, 10,000 lbs (6es)	138,000	7,716
Truck Fork Lift R/T 10,000 1bs	s (4ea) 90,000	8,400
Kir - Flatbed Trailer (6ea)	48,000	1,590
99 Forms and Publications	57	4

NAVAL FACILITIES ENGINEERING COMMAND

FACILITIES

FACILITY OR GROUP	ASSEMBLY OR ECC		NORTH (TEMPERATE)	TOTALS
		QTY	WEIGHT LBS	CUBIC FT
141 12E	Air Cargo Terminal	1	1,608,075.64	37,399.41
812 30E	Electrical Distribution Lines- Ugnd	1	3,678.30	89.46
832 10BP	Sanitary Sewer 4 Inch 300FT	1	641.98	46.69
842 10AN	Water Distribution Line Potable	1	335.54	19.53
843 10H	Fire Protection Pipeline	1	27,629.93	775.95
851 10A	Road with Drainage 1 mile	1	44,988.00	1,947.00
	CIVIL ENGINEER SUPPORT	EQUIP	ENT (CESE)	
030731	Trk 3/4 Util	2	11,000.06	1,280.00
058812	Trk 5T Cargo Ml	4	88,576.00	8,260.00
073101	Trk LDR AC HILF	1	22,700.00	1,500.00

1. MISSION

The Fl Cargo Handling Battalion (CHB) is a multi-mission unit comprised of 8 officers and 145 enlisted personnel plus the basic unit equipment required to provide technical and supervisory cargo handling capability to fleet and area commanders in support of world-wide naval operations. Unit equipment requirements beyond the basic allowance of personnel support equipment are provided to the cargo handling battalion by one or more of the supplemental equipment packages (FlA through FlG) described below. These supplemental equipment packages are tailored to the specific mission environment and to the specific requirements of the mission. The utilization of these supplemental equipment packages provide the fleet commanders a wide variety of options in utilizing the cargo handling battalions.

Units Assigned to the ABFC Fl Mission. The following units have the capability of being assigned to the ABFC Fl functional mission:

- 1. The Navy Cargo Handling and Port Group
- 2. The Naval Reserve Cargo Handling Training Battalion
- 3. Naval Reserve Cargo Handling Bartalions

Both the Navy Cargo Handling and Port Group (NAVCHAPGRU) and the Naval Reserve Cargo Handling Training Battalion (NR CHTB) are active duty battalions and are always available. The Naval Reserve Cargo Handling Battalions (NR CHB's) are comprised solely of selected reserves and require a slightly longer time period to employ.

Cargo Handling Battalien Tasks. The specific tasks of a cargo handling battalion include, but are not limited to:

MPS/AFOE Cargo Handling. Providing skilled stevedores and command and control personnel capable of loading/discharging (either in-stream or pierside) commercial/MSC cargo ships associated with a maritime prepositioning ship (MPS) operation or an amphibious assault follow-on echelon (AFOE).

Heavy Lift Marine Crane Operators. Providing shipboard heavy lift crane operators for MPS, containership, auxiliary crane ship (TACS) and other specialized operations.

Total Cargo Class Responsibility. Providing stevedores and command and control personnel capable of loading/discharging all classes of cargo, including munitions, in a developed of non-developed port or in stream.

Limited Ocean Terminal. Providing managerial and technically skilled personnel capable of operating a limited marine cargo terminal in support of ship loading/discharging operations.

Limited Air Terminal. Providing managerial and technically skilled personnel capable of loading/discharging cargo from commercial and military aircraft and operating a limited air cargo terminal.

Self Supporting. Providing own services to sustain the administration, messing, berthing, limited construction, organizational level maintenance and repair requirements of the Fl ABFC unit.

Cargo handling battalions operate most effectively when employed solely in ship loading and discharge operations and when each of the 16 hatch teams is augmented by 7 unskilled (strongback) personnel from the supported activity. When augmented with 112 personnel (7 per hatch team) from the supported unit, the cargo handling battalion can achieve a 2880 measurement tons per day discharge rate alongside the pier and a 1920 measurement tons per day discharge rate in stream. If the cargo handling battalion is not augmented, then the discharge rates must be reduced by fifty per cent (1440 measurement tons at pierside and 960 measurement tons in stream).

The required number of cargo handling battalions (ABFC F1) units is directly dependent upon:

1. Tonnage to be handled.

2. Discharge scheduling and discharge rate desired.

3. Number of vessels/aircraft to be discharged/loaded.

4. Available pier and related facilities. (pierside operations)

5. Lighterage and related facilities (in-stream operations)

6. Available indigenous labor.

7. Available strongback labor augmentation.

8. Available mechanized cargo handling equipment (may be attained by utilizing a supplemental equipment package or combination of packages (FlA through FlG)

PLANNING ASSISTANCE AND MISSION DEVELOPMENT - The F1 Cargo Handling Battalion, and its associated supplemental equipment packages (F1A through F1G), provides the widest possible flexibility in the employment of cargo handling battalions. The Navy Cargo Handling and Port Group and the Naval Reserve Cargo Handling Battalion Regimental Staff (NR CHB REG STAFF) are available to provide fleet and area commanders with technical planning assistance in programming F1 Cargo Handling Battalions into specific mission scenarios.

For planning purposes the Fl Cargo Handling Battalion may be programmed with a variety of equipment packages tailored to specific mission scenarios as follows:

Fl - Cargo Handling Battalion Personnel and Core Equipment UCHBA

This package provides the personnel and the basic personal support equipment required to work all cargo handling situations. This package is required for all scenarios.

Supplemental Equipment Packages (added on to the basic Fl unit above to meet the environmental and mission requirements of specific missions):

FlA - Expanded Core Equipment Package

UCHBB

This package provides the equipment necessary to support one Cargo Handling Battalion in mission scenarios other than the MPS scenarios. This equipment package must be provided to all Cargo Handling Battalions in all mission scenarios other than the MPS scenarios.

F1B - Cargo Handling CESE Package

UCHBC

This package provides the civil engineering support equipment (trucks, trailers, etc.) necessary to support a cargo handling battalion in establishing or augmenting a port. This package of equipment should be provided to a battalion in all ports where CESE is not locally available. (Note: This package provides the CESE for pier, terminal and local delivery operations. It does NOT provide a line haul capability).

FIC - Cargo Handling MHE Package

UCHBD

This package provides the NAVSUP materials handling equipment (forklifts, etc.) necessary to support an Fl Cargo Handling Battalion in a port where MHE is not locally svailable.

FID - Container Handling Crane/Equipment Package

UCHBE

This package provides the mobile crane container handling forklift and supporting equipment necessary to support an Fl cargo handling battalion in a port that does not have locally available container handling facilities and where it is desired that the cargo handling battalion offload/load container ships and operate a container marshalling yard adjacent to the ocean terminal.

FlE - Air Cargo MHE Equipment Package

JCHBF

This package provides the equipment necessary to support one detachment of an Fl Cargo Fandling Battalion in the operation of an air cargo terminal. This equipment package should be programmed into all scenarios where it is anticipated that the Fl Cargo Handling Battalion will be required to operate an air terminal. If air terminal operations will require more than one detachment of the Fl Cargo Handling Battalion then one FlE equipment package must be provided for each detachment.

FIF - Expeditionary Tent Camp Equipment

UCHBG

This package provides all the equipment necessary for one Fl Cargo Handling Battalion to establish and operate an austere expeditionary tent camp to provide berthing and messing for its personnel. This package of equipment should be provided to each Fl Cargo Handling Bettalion in all scenarios where berthing or messing is not locally available or where berthing and messing is not provided by another activity or AETC unit.

FIG - Camp Support CESE Equipment

UCHBH

This package provides the Civil Engineering Support Equipment (CESE) necessary to construct and maintain an austere expeditionary tent camp to billet and subsist one Fl Cargo Handling Battalion. This package contains only the camp support equipment. All other CESE equipment to be used in cargo handling operations is listed above under the FlB supplemental package.

BASIC FI CARGO HANDLING BATTALION MISSIONS

While the Fl Cargo Handling Battalion is a multi-mission unit with a wide variety of possible missions, there are three major mission scenarios which the battalion is normally programmed to accomplish.

Maritime Prepositioning Ships (MPS) Support

The Fl Cargo Handling Battalion provides the personnel and equipment necessary to provide technical and supervisory cargo handling capabilities to fleet and area commanders in support of the Maritime Prepositioning Ships (MPS) program. The Fl component provides the skilled stevedores and command and control personnel capable of loading/discharging commercial and MSC ships in both an open ocean and pierside environment. Component personnel and organic equipment are transported by MAC as part of the Fly In Echelon (FIE) of the Navy Support Element (PSE) to the selected beach or port where the MPS squadron has been deployed. Each MPS squadron consists of 4 or 5 specially configured merchant ships which carry the majority of combat equipment and 30 days supplies for a Marine Amphibious Brigade (MAB). Hatch boxes with cargo handling equipment are prepositioned onboard each of the ships. Each MPS squadron requires two each Fl Cargo Handling Battalions to provide discharge of the cargo in the stream or pierside within the currently required timeframes. Each Fl Cargo Handling Bittalion must be augmented with 112 USMC strongbacks if the discharge timeframes are to be met. Upon completion of the MPS offload, one of the F1 Cargo Handling Battalions may be retained on site to provide continuing/resupply cargo discharge services while the other cargo handling battalion may be redeployed to another cargo handing mission. Both cargo handling battalions will require additional equipment from one or more of the Supplemental Equipment Packages (FIA through FIG) depending on the subsequent mission assignments.

PLANNING GUIDANCE - MPS MISSION: Program the following packages for the MPS mission:

- A. 2 each Fl Cargo Handling Battalions for each MPS Squadron (no additiona Supplemental Equipment Packages are required for the MPS mission)
- B. 224 strongback personnel from the supported unit (USMC) to augment the CHBs

Assault Follow-On Echelon Mission Support

Each F1 Cargo Handling Battalion is capable of discharging cargo to support one half of a Marine Amphibious Brigade (MAB) within the paired timeframes when augmented with the F1A Expanded Core Equipment Package. The required multiples of the F1 Cargo Handling Battalion (2 each CHBs for a MAB level AFOE and 4 each CHBs for a MAF level AFOE) plus the required quantities of the supplemental equipment packages (2 each F1A packages for the MAB level AFOE mission and 4 each F1A packages for the MAF level AFOE mission) provide the required technical and supervisory cargo handling capabilities to fleet and area commanders in support of USMC amphibious assault operation (MAB/MAF). The AFOE carries sufficient equipment and supplies to sustain 60 days of combat and consists of unit equipment and supplies which are not essential for the initial amphibious assault. Component

personnel and organic equipment accompany the AFOE to the area of operation. USMC personnel will augment the Fl Cargo Handling Bottalion in the unskilled positions at the level of 224 augmentees for a MAB and 448 for a MAF level AFOE. The Naval Beach Group will provide required CESE, MHE and messing/berthing for the CHB, under the AFOE scenario by means of Table of Allowance Number 56 (TOA 56).

FLANNING GUIDANCE FOR AFOE MISSION - The number of F1 Cargo Handling Battalions and the required number of F1A supplemental equipment packages depend upon the size of the APOE:

MAB Level AFOE requires:

- A. 2 each Fl Cargo Handling Battalions
- . 2 each FIA Expanded Core Equipment Packages
- C. 224 strongback personnel from the supported unit

MAF Level AFOE requires:

- A. 4 each Fl Cargo Handling Battalions
- B. 4 each FlA Expanded Core Equipment Packages
- C. 448 strongback personnel from the supported unit

Port or Terminal Operation Augmentation of Establishment

The Fl Cargo Handling Battalion, when provided with the necessary supplemental equipment packages based upon the specific environment and the required strongbacks, provides the unit equipment, skilled stevedores and command and control personnel to augment or establish a port operation with a basic palletized cargo dischage rate of 2880 measurement tons per day. Specific tasks of the cargo handling battalion include, but are not limited to:

a. Cargo Handling

Providing stevedores and command and control personnel capable of offloading/discharging commercial and MSC ships, including munitions handling, in a developed port. When all palletized cargo handling operations are pierside the discharge rate will be 2880 measurement tons per day. When all cargo handling operations are in stream the discharge rate will be 1920 measurement tons per day.

b. Ocean Cargo Terminal

Providing 35 managerial and skilled technical personnel capable of operating a temporary ocean cargo terminal associated with the ship discharge. The maximum through put rate of the marine terminal will be 240 measurement tons per hatch team per day and the rate of the ship's discharge will be reduced accordingly.

c. Limited Air Terminal

Providing a detachment of 15 managerial and skilled personnel to operate a limited air cargo terminal. The detachment provides the battalion with the capability of sustaining around the clock operations at the limited air

cargo terminal. The establishment of the limited air cargo terminal will reduce the ship discharge rate to 2700 measurement tons per day pierside and to 1800 measurement tons per day in stream. The establishment of a limited air cargo terminal requires one FIE supplemental equipment package.

d. Crane Operators

Providing 32 heavy lift crane operators for containership, TACS vessels, or other special operations. The discharge rate of TACS vessel operations is 48 containers per day (12 hour) per hatch team pierside and 36 containers per day (12 hours) per hatch team in stream.

e. Mobile Shore/Container Crane Operations

Providing 12 mobile shore crane operators to offload containers pierside or to operate a terminal marshalling yard. The assignment of the mobile shore container crane task requires the addition of an FID Container Handling Crane/Equipment Package to the F1 Cargo Handling Dattalion.

f. Expeditionary Tent Camp

The Fl Cargo Handling Battalion is capable of providing its own messing, berthing and limited base support functions for short periods of time (less than 90 days) when provided with the FlF Expeditionary Tent Camp supplemental equipment package.

PLANNING GUIDANCE FOR PORT ESTAELISH/AUGMENT OPERATIONS - The following components must be programmed for each 2880 measurement tons of cargo desired discharged daily pierside and for each 1920 measurement tons of cargo desired discharged daily in stream:

- 1 each Fl Cargo Handling Battalion
- I each FlA Expanded Core Equipment Puckage
- I each FIB Cargo Handling CESE Equipment Package (must be provided only when adequate CESE equipment is not locally available in the port)
- 1 each FIC Cargo Handling MHE Equipment Package (must be provided only when adequate NHE is not locally available in the port)
- l each FID Container Handling Crane/Equipment Package (must be provided if container handling operations are desired and container handling equipment is not available in the port)
- I each FIE Air Cargo MRE Equipment Fackage (must be provided when a limited air cargo terminal is planned and there is not sufficient air cargo MRE available locally)
- I each FIF Expeditionery Tent Camp Equipment Package (must be provided if messing and berthing is not locally available or is not being provided by stother command)

CARGO HANDIING BATTALION PRODUCTIVITY FACTORS

Note: All per hour are rounded to nearest .1 MT. All per 12 hour
Figures are rounded to nearest 5 MT.

Pier discharge	Per Hour Per Hatch Team (14 man)	Hatch Team (14 man)
Palleti ed Cargo	15 NT	180 MT
Break Bulk Cargo	6.2 MT	75 MT
Mixed Cargo	10.6 MT	130 MI
Pier Ship Loading		
Palletized Cargo	2.8 MI	105 MI
Break Bulk Cargo	4.1 MT	50 MT
Mixed Cargo	o.4 mT	75 MT
In Stream Ship Discharge		
Palletized Cargo	19.00 MT	120 MT
Break Dulk Cargo	5.6 MT	70 MI
Mixed Cargo	7.8 MI	95 MT
In Stream Ship Loading		
Pailetized Cargo	6.7 MT	80 NI
Break Bulk Cargo	3.6 MT	45 MT
Nixed Cargo	. 5.7 MT	60 MT
Container, TACS, Jumbo Ri	lg, Ecavy Lift Operation	13
Pier Load and/or Disc	thange 4 Containers (126 MT)	48 Containers (1536 MT)
Stream Load and/on Di	scharge 3 Containers (96 MT)	36 Containers (1152 MT)
Ocean Term al (Palletize	d Cargo)	
Through Put (Receive	and Issue) 20 hT	240 MT
One Way (Receive or I	sene) 40 MT	480 MT
Air Terminal (measured in pounds v (463L max weight=10,0		80,000 LBS (10-II 463L Plt)
Pier Operation	45 MT	540 MT

Cargo Handling Battalion Utilization Tables

Noces

- 1. 16 batch teams assumes augmentation of 112 stronbacks (7 per hatch team). Without augmentation, the cargo capacity is reduced by 50%.
- 2. Above figures assume unitized (completely on pallets) cargo. Rough conversion factors for other classes of cargo are:
 - a. Break Bulk * 50% of the palletized cargo capacity
 - b. Mixed Cargo = 75% of the palletized cargo capacity
- 3. Ship operations Divide hatch team by 4 to determine the number of hatch teams working each ship on each shift (eg. 2 ship 16 hatch teams means 4 hatch teams per shift per ship).

Ship Discharge for Palletized Cargo (in measurement tons)

	Pier Side	In Stream	Fier Team	Ocean Terminal	Air Terminal
2 ship	2080 MT (16 HT)	O	0	Ü	G
2 ship	2160 MT (12 HT)	0	2160 MT (4 HT)	0	e
l ship	1440 MT (8 HI)	0	1620 MT (3 HT)	1200 MT (5 HT)	0
1 ship	1260 MT (7 FT)	0	1620 MT (3 HT)	1200MT (5 HT)	89,000 1bs (1 PT)
2 ship	o	1920 ht (16 Ht)	· 0	O	0

Ship loading of Palletized Cargo (in the surgent tons)

	Pier Side In Stream	Pier Team	Ocean Terminal	Air Terminal
2 ship	1680 MT 0 (16 HT)	С	c	0
2 sh1p	1365 MT 0 (13 HT)	1620 MT (3 HT)	ð	0
l ship	1050 MT 0 (10 HT)	1080 MT (2 HT)	960 NT (4 HT)	0
1 ship	1050 Mi 0 (10 HT)	1080 MT (2 MT)	720 MT (3 MT)	80,000 lbs (1 ET)
2 ship	0 1280 MT (16 MT)	0	9	O

Container Loading and Discharge (measured in number of containers) (using TACS, MPS, shore crane, etc.)

	Pier Side	In Stream	Pier Team		Air Terminal
2 ship	768 (16 HT) (24,576 HT)	0	0	0	ė.
2 ship	576 (12 HT) (18,432 HT)	О .	576 (4 HT) (18,432 MT)	c	С
qida C	432 (9 HT) (13,824 MT)	0	432 (3 ET) (13,842 MT)	432 (4 HT) (13,824 MT)	0
Z ship	584 (8 HT) (12,283 MT)	o	432 (S.Em) (13,824 MT)	432 (4 HT) (13,824 HT)	ed, 000, 03 (TT 1) (50 ET)
2 ship		576 (16 HT) (18,432 MT)	,		

Fersonnel Assignments

Available = 145 (CHB) + 112 (stongback augmentees) = 257 for 2 ships, 2 shifts

Hatch leam (224 personnel)

Ratch Captain	1
Hold Boss	1
Crane/Winch Operator	2
Signalman	1
Forklift Operator	2
Stevedores (Augmented)	7

14 per hatch team

Personnel Assignments (continued)

b. Command and Control (14)

Technical Supervisor	1
Ship Supervisor	2
Status Center Watch	2
Communications/Security	2
Duty Corpsman	2

9 per shift = 14 per battalion

c. Support Personnel

Mechanics	2
Corpsmen	2
Cooks	7
Camp Support	4
Administration	2

17 per bettalion

BASE SUPPORT. While the cargo bandling battalion is capable of limited sustere self support for extended periods of time it is more desirable for the area or base headquarters organization to provide bousing, messing, medical and welfare support for operations of greater than 90 day duration. When the cargo handling battalion will not be supported by a base organization and will be required to operate for more than 90 days in an isolated area, order the following components:

Housing and messing - Appropriate N (Tent Camp) component to support specific operations.

Ships Store - Use appropriate D24 series (Ship Store Facilities)

Medical Facilities - Use M15E (Dispensery, 10-bed, Mobile) component and M17E (Dertal, Mobile) component if required.

Motion Pictures - Use N23 (Motion Picture Projection) component for film operation and exchange with ships or local activities.

Trucking - The Fl ABFC provides trucking assets over short distances (less than ten miles) from the pier/beach to the ocean terminal. If longer line haul trucking support is desired, a Pl7 Trucking Unit should be programmed.

2. PERSONNEL 8 Officers 145 En isted Men Total 153

			OFFICE	RS		ENL)	STED >	ŒN	
Ech	No	Rank	Desig	Billet Rate	Gp	Pay Gr	PNEC	SNEC	Title
1	1	CDR	3105						Commanding Officer
ì	ī	LCDR	3105						Executive Officer
î	ī	LCDR	3105						Operations Officer
ī	ĩ	LT	3105	•					Ops Watch/Training Off
ī	ī	LT	3105						Ops Watch/Shipload Off
ī	ī	LT	3105						Air Cargo/Comm Off
ī	1	LT	3105						Marine Term/Security Off
1	ī	LT	5105						Engineering/Facilities Of
1	2			ABH2		5			Air Cargo/Forklift Driv
1	2			BMCS		8			Tech Cargo Supervisor
1	6			BMC		7			Hatch Captain
1	10			BMI		6			Hatch Captain
1	2			BM1		6			Hold Boss
1	12			BM2		5			Hold Bosa
1	15			BM3		4			Signalman
1	20			BM3		4			Winch/Crane Operator
1	1			BUl		6			Facilities Supervisor
1	2			Eug		4			Builder/Forklift Driv
1	2			CE2		5			Watch Electrician/Forklift
1	2			CE3		4			Duty Electrician/Forklift
1	1			CMC		7			Transportation Supvr
1	1			CMI		6			Maint Shop Supvr/Fork Dr
1	2			CM2		5			Maint Watch Supvr/Fork Dr
1	4			CM3		4			Mechanic/Driver/Fork Dr
1	2 2			E02		5			Dispatcher/Driver
1	1			E03		4 5			Driver/Equip Operator
i	2			GM2 HM2		5			Armorer/Security Supvr
î	2			HM3		4			Medical Duty Supvr
i	ì			MSC		7			Duty Corpsman
ĭ	2			MS 1		6			Messing Supervisor Galley Warch Captain
ī	4			MS3		4			Galley Watch Cook
1	i			SKCS		8			Terminal Supervisor
1	2			SK1		6			Hold Boss/Document Supvr
1	4			SK2		5			Winch/Crane Oper/Document
1	2			SK2		5			Pier Boss
1	8			SK3		4			Winch/Crane Operator
Į.	16			SK3		6			Forklift Driver/Documntor
1.	4			SK3		4			Pier Driver/forklift Dr
L	1			UT2		5			Plumber/Facilities Maint
ļ.	1			YN 1		5			Administrative Div Supr
,	1			YN2	5	5			Office Supr/Status Ctr Wat
!	1			YN2		5		(Clerk/Personnel Asst
	3			YN3	4	•			Clerk/Status Ctr Watch

3. COST

NAVAIR .		***
SPAWAR	\$	1,628
NAVFAC	•	2,990,928
NAVSEA	Š	
NAVSUR	,	1,052,229
NSF	\$	
	Ą	2.30, 109
NAVFAC		10 551
ldentified (Other) Ş	40.554

4. CONSTRUCTION

Tents or huts

Area required - 5 acres

Prefab building - 2,880 sq ft

Space requirements for Admin and Office - 1920 sq ft

Operations - 960 sq ft

Power required 20 KW

Internal roads and parking - 3,500 sq yds

Total Component material - 693 LT's, 1,759 MT's

Construction time - 516 M-Days

5. MATERIEL (MAJOR ITEMS)

Housing - Three 20 x 48 ft buildings
Materials handling trucks
Transportation
Landing mat
Ammunition handling equipment
Spark proof hand tools
Construction equipment and consumables
Hand tools and consumables
Office equipment and supplies

WEIGHT: U/D CUBE: U/D

NAVAL SUPPLY SYSTEMS COMMAND

Sub-Function Codes

Ref	Description	VT	CU
10	Damage and safety control material	243	8
11	Administrative equipment and supplies	14,472	777
	Personnel equipment and sundries	5,461	744
	General equipment and supplies	153,754	, 143
	Communications equipment and supplies	80	5
		23	.3
	Non-medical support for medical & dental	equip 1	. 1
	Ordnance support items	10,371	639
	Fuel for heating	30,150	77 7

NAVAL SUPPLY SYSTEMS COMMAND (CONTINUED)

Ref	Description	WI	cu	
86	Fuel for vehicles and equipment under			
	32 deg	210,854	5,464	
87	Fuel for vehicles and equipment over	•	ŕ	
	32 deg	210,854	5,464	
88	POL for under 32 deg	12,226	312	
89	POL for over 32 deg	12,352		
91	Material Handling equipment	·		
	Battery 18 coll 21 plate 36V - 29 ea	68,904	397	
	Charger battery 36V - 6 ca	3,072	72	
	Trailer platform 48 X 108 - 4 ea	4,000	324	
	Truck, forklift diesel 4,000 lb RT - 14 ea	104,790	4,312	
	Truck, forklift diesel 16,000 1b RT - 5 ea	150,000	10,650	
	Truck, forklift electric 4,000 lb - 9 ea	112,500	2,700	
	Truck, acft cargo 40,000 lb - 2 ea	94,000	3,200	
	Truck, acft cargo 25,000 lb - 2 ea	46,000	2,572	
99	Forms and publications	378	18	
	NAVAL MEDICAL COMM	AND		
42	Medical Assembly M-360	1,431	94	
	NAVAL SEA SYSTEMS CON	1MAND		
	U/I	QTY	WT	CU

*Weight and cube reflected by NAVSUP S/F 80
Ammunition (Refer to NAVSEA Ammunition Allowance List 38736 and NAVSEA INST C8011.2. (Ammunition is handled separately from the component)

141

Pistol, Cal 45 M1911A1 Rifle 5.56MM, M16A1

NAVAL SEA SYSTEMS COMMAND (CONTINUED)

	υ/I	QTY	VT	CU
High Dose Dosimeter 1M-1431PD	ea	6	3	1
Casualty Dosimeter DT-60/PD	ea	307	18	_
Casualty Dosimeter CP-95()PD	ea	2	100	6
Dosineter Charger PP-354()PD	ea	2	2	1
Long Range Survey Meter AN/PDR-27	ea	3	1.95	3
High Range Survey Meter AN/PDR-43	ea	3	36	1

SPACE AND NAVAL WARFARE SYSTEMS COMMAND

EQUIPMENT	PART NO.	QTY.
Standard Communications		
Horizon Hand-Phone JI		
Radio unit	HX200S	60
VHF Flexible Antenna	AT154	60
Ni-cad Battery Pank	CNB6 .	60
Wall Charger	CWC25	60
Earphone	EP1	60
Plastic case	•	60
Mini Lapel Speaker Mic	MP635G	60
Desk Top "Fast" Charger	CSA20	60
Ni-cad Battery Pack	CNB7	60
Waterproof Bag	EWA*	60

^{*}EWA is the brand name for this part. This brand of bag is recommended over the Standard Communications version.

AN/PRC-77 Radio SET		
Radio Receiver-Transmitter	5820-00-930-3724	13
Battery Box		13
Antenna	5820-00-889-3803	13
Autenna	5820-00-242-4967	13
Handset	5965-00-069-8886	1.3
Antenna Support	5985-00-086-7149	13
Electrical Equip. Harness	5820-00-892-8094	13
Cotton Duck Bag	5920-00-086-7138	13
AN/PR -113(V)-3 Radio Set	706738-803	4
Radio Assemby RT-1319/URC	914858-803	4
Battery Case Assembly	810590-801	4
VHF Antenna	812057~1	4
UHF Antenna	812058-1	4
TOD Transfer Cable	566083-808	4
KY57 Baseband Cable	566084-308	4,
Operator Handbooks		4
Handset H-250/U GFE	5965-00-043-3463	4

SPACE AND NAVAL WARFARE SYSTEMS COMMAND (CONTINUED)

EQUIPMENT	PART NO.	QTY.
	412E 01 024 27/23	8
Battery BA5590/U	6135-01-036-3463	
Battery BB5590/U	6140-01-063-3918	24
Pack Frame	8465-00-001-6475	4
Field Fack	8465-01-019-9102	4
Battery Charger	PP7236	4
Antenna UHF/VHF	812059-1	4
AN/PRC-104(V) Radio Set	5820-01-141-7953	4
RecTrans. RT-1209/URC	5820-01-141-7953	4
Amplifier 4M-6874/PRC-104	5820-01-065-5044	4
Cable CY-8291/PRC-104(V)		4
Cable CY-7875/PRC-104	6135-61-080-2886	4
Cable CX-13030/PRC-1C4		4
Ceble CX-13031/PRC-104		4
Charger Cable Assembly	6135-01-092-4807	4
Antenna AB-1241/PRC-104	5820 -01-065-4495	žą.
Cable CG-3815/U	05869/755002A7114-1	4
Ant. Section-AB-129/FR	5820-00-234-4127	4
	5985-00-646-2365	4
Antenna AT-271A/PRC	3983-00-040-2303	4
Instruction Card	896900-001-6476	4
Cargo Support Shelf	8465-00-001-6577	4
Cargo Tiedown Strap		4
Pack Frame	8465-00-001-6475	4
Field Pack	8465-01-019-9102	4
Adapter UG-349 ()/U	5935-00-204-5110	5
Lithium Battery BA 5590	6135-01-036-3945	
Storage Batterh BA 590	6140-01-063-3918	16
Immers. Res. Loudspeaker	5965-00-876-2375	4
RF Cable Assembly	05869/755002B9016	4
Audio Cable Assembly	05869/755002B9017	4
Antenna AS-2259/GR	5985-00-106-6130	ů.
Handset H-250/U	596500-043-3463	4
Cable Assembly	05869/755002B9018	4
Battery Charger PP-7286	6130-01-141-3490	4
Universal Power Supply		4
AN/VRC-46 Radio Set	7G5820-00-223-7453	5
RecTrans.	RT-524/VRC	5
Power Supply	FP-2953/U	.5
Mntg Base MT-1029/VRC	5820-00-893-1323	
Antenna Urit	AS-1729/VRC	5 5
Antenna Element	AT-1095/VRC	5
Antenna Element	AS-1730/VRC	5
Matching Unit/Base	MX-6707/VRC	5
NAVELEX Technical Manual	0967-467-3010	5
	0,0, 40, 5010	5
Cable Assembly CX-4722		5 5
Cable Assembly CX-4720	9N5965-00-243-6420	5
Loudspeaker LS-166/U	7N 270 27 007 44.27 0440	J

SPACE AND NAVAL WARFARE SYSTEMS COMMAND (CONTINUED)

**Cable assembly stock numbers and prices will vary with length. Exact lengths will need to be identified before stock numbers and prices can be quoted.

NOTE: The AN/VRC-46 radio operates on a 24 volt supply. Since NAVCHAPCRU vehicles operate with 12 volt systems, it is is recommendated that an extra 12 volt battery be purchased and installed in series with the existing battery in all vehicles requiring this radio.

NAVAL FACILITIES ENGINEERING COMMAND

FACILITIES

FACILITY			NORTH (TEMPERATE)	TOTALS
OR GROUP	OR ECC	O TTTV	HETCHT IDC	CUBIC FT
210 5004	Present Character Char Treatent	QTY	WEIGHT LBS 25,066.32	773.57
218 50TA		1 2		
610 10N 723 20J	Administration Minimal		2,972.28 10,396.86	229.64 494.19
812 30PE	Head 4-Hole Burn Out w/soakage Elec Distr Line 1000ft #t EXPED		1,075.28	40.00
		1	.00	.00
852 10C	Parking Area 7000 SY	¥	•00	.00
	CIVIL ENGINEER SUPPOR	T EQUIF	PMENT (CESE)	
036031	Trk 11T Cargo	7	42,000.00	5,250.00
036131	Ambulsace Heavy	1	7,475.00	1,053.00
058712	Trk 5% Dump MIL	1	23,640.00	1,620.00
058812	Trk 5T Cargo ML	2	44,788.00	4,130.00
060712	Trk 5T Trac ML	12	231,120.00	18,192.00
070921	Trk Fld Servng 4X2	1	14,110.00	1,450.00
074611	Trk Tank 1200 gal	3	43,875.00	4,035.00
081601	Sami 20-T Stake	10	109,000.00	13,560.00
082601	Semi 50-T Lobed	2	32,570.00	3,734.00
088002	Trlr TK 400 gal	5	14,000.00	3,250.00
453109	Loader Scoop (w/backhoe)	1	23,000.00	€80.50
511022	Floodlight Set	8	30,400.00	3,984.00
512111	Gen 15KW Skid	2	6,000.00	105.00
512211	Gen 30KW Skid	1	3,500.00	60.0⊝
821901	Crane Trk 140T	1	198,500.00	5,136.00
825302	Crane Trk 30T	1	72,200.00	5,720.00
Officer die	Loader, Container, Front End	1	4. Melle Later Manne	
	Top Pick			
America and	Spreader, Semi-auto 20 fc	1	Shar mountain	min maker (1983)
MA-star-see	Spreader, Semi-auto 40 ft	1	other same state	يهري طمير والان
	TOOL KI	TS		
80013	Kit Mech Hand Tools 1/2 Men	4	1,376.48	84.12
80015	Kit Battery Service Tools	1	516.98	11.82
w w w # -	and the second of the property of the second	-		

1. MISSION

This is a mobile, shore-based facility that provides Intermediate Level Maintenance Repair Capability for a nine aircraft P-3 A/B Squadron deployed to an advance base for extended operations (greater than 30 days). If operations beyond 30 days but less than 90 days are expected at the deployment site and adequate Supply Lines of Communications (SLOC) are available, this ABFC need not necessarily be deployed in its entirety. Only those modules (elements) herein which provide the battery shop/s, support equipment, support equipment maintenance, oxygen/nitrogen recharging and pre-positioned codes P&E IMRL equipment capabilities are required. However, if adequate SLOC are not available or if operations are planned beyond 90 days, it should be fully deployed.

This ABFC is required on a one per site basis, if more than one squadron is to be supported, early visibility is required in order that the component can be tailored upward to support the additional workload. Additional spares and repair parts, and selected support equipment and personnel will be required, especially if the additional workload is generated by an off-station squadron/detachment.

This facility consists of sixty-one 20 ft by 8 ft by 8 ft mobile vans and a rapidly erectable, portable, arch-type building to house full avionics repair capability, including PME/CAL and micro-min repair, and selected airframe/power plant repair capability, necessary maintenance control, Supply Support Center, and administrative support spaces, technical library, maintenance forms and publications, adequate rotable pool material and adequate OSI for maintenance of the facility. Selected airframe/power plant repair capabilities are:

- a. Airframes Eusential hydraulic/pneumatic repair, non-destructive testing, tire disassembly/build-up, corrosion repair, welding, and sheet metal fabrication/repair. Oxygen/nitrogen will be separately provided in 400 gallon air-transportable containers with vaporization/cylinder recharging provided via a single mobile facility.
- b. Power Plants Engine repair capability includes Level III engine build-up, including replacement of turbine assemblies. QECA support includes one complete QECK to be fitted to a canned nude engine. The QECA provided in the squadron's 30 day contingency support package will become a supply asset of this component when collocated with the deployed squadron. Propeller repair capability consists of disassembly/build-up, repair of de-icer elements, dome re-seal, propeller control external leakage repair including propeller and seal plate build-up. One complete spare propeller (including propeller assembly and controls) is provided with this component. The build-up propeller provided in the squadron's contingency support package will become an asset of this component when collocated with the deployed squadron. Two spare gear reduction assemblies are included in this component. Auxiliary Power Unit (APU) maintenance will be limited to component or end item replacement only.

Battery shop cludes capabilities for atoring and servicing both NICAD and lead/acid type. An adequate initial supply of spare batteries of both types is included.

The component is composed of individual modules designed to provide support to specified systems/equipment and/or provide specific shop/work center support. The mainstant the mobile facilities, personnel, support equipment, ancillary equipment, and parts/materials necessary to provide Intermediate level maintenance support for the sircraft systems/equipments intended. Modularization of this component allows a phased build-up thus minimizing the necessity for massive initial transport requirements.

This component, when added to the P-3 Squadron (Common) Support ABFC, if required, and the squadron's organic capability, will provide all necessary maintenance support for a single VP squadron operating at projected wartime flight hours.

This component is composed of 12 modules capable of specified functions in the intermediate maintenance support of P-3 sircraft systems and airborne equipments. Missions of each of the modules, their recommended assigned Unit Types Codes (UTC), number of mobile facilties, and approximate weight and cube are described as follows:

TITLE	MISSION	UTC	No. MFs	WT(LT)	CU(MT)
Mechanical Support following capabilit		9523 A	14	142.4	512.0
Tire Shop		wheel and tir		ace for ai	craft
Airframes		metal and fill repair and washops.			
Power Plant/ Propeller Shop	of p∪wer : limi ed c	gearbox/torquection, suxionponent/end	liary power item replac	unit (APU ement, and	;) I
Non-Destructive Inspection (NDI)		eircraft and ve inspection		ipment nor	ı -
Support Equipment/MI Maintenance shops	(other the intermedia	servicing and in avionics) ite levels of i incillary e	used by org	anizations e of MFs 3	1 and
Battery Shop Support following capabiliti	.68 =		2	17.8	64.C
	Provides l	ead-acid and	NI(AL) Datt	ery baudli	ng,

storage, servicing and recharging.

Tool Room Support Module. Includes following capabilities -Provides administration/control of maintenance, storage/maintenance of technical data, working space for Quality Assurance personnel, and secure storage/issue of tools and other equipment. Liquid Oxygen/Nitrogen Support Module. 9523R 1 3.9 32.0 Includes following capabilities -Provides for generation and distribution of gaseous oxygen and nitrogen. Supply Support Modules. Includes 9523L 11 116.6 664.9 following capabilities -Provides management and compartmentalized storage of AVCAL/GSI material and upline asset and functional capabilities management information. *Note 3. Reder/ESM/IRDS Support Modules. 9523N 3 26.7 96.0 Includes following capabilities. -Provides test, check and repair of radar/ESM/IRDS systems and associated equipment. COM/NAV Support Module. Includes 9523P 26.7 96.0 following capabilities -Provides COM/NAV (including communications security EQ) and associated equipment test and check of repair. INS Support Module. Includes 95230 8.3 32.0 following capabilities -Provides inertial navigation systems, electrical instruments and associated equipment test, check and repair. ASW Support Modules. Includes 17.8 64.0 9523R 2 following capabilities -Provides ASW systems test, check and repair. 192.0 53.4 PME Calibration Support Module. 9523T 6 Includes following capabilities -Provides test equipment repair and Type IV field calibration. ATE Support Modules. Includes 9523V 53.4 192.0 following capabilities -Provides test, check and repair of general

9523P

25.7

96.0

Production Control, Technical Library,

avionics equipment supported by the AN/USM-449.

Micro-Min Support Module. Includes

9523X

1

8.9 32.0

following capabilities -

Provides test, thack and repair of general avionics equipment.

- NOTE: (1) Integration Units may or not be required when developing individual modules, depending upon deployment site facilities available.

 There are eight integration units assigned to each complex. Weight and cube of each unit is 8.9 LT and 32 MT, and the total weight and cube is 71.2 and 256 MT.
 - (2) Additionally, a separate rapidly erectable and relocatable building is included to be shared by the Power Plant/Propeller and Support Equipment Shops. The building is a rigid frame, membrane covered type structure which is currently under development. Weight and cube is included in the Fower Plant and Propeller Shop Module (17.8 LT and 64.0 MT).
 - (3) Weight and cube includes 18.7 LT and 143.9 MT for items too large for storage in mobile facilities.

2. PIRSONNEL:

2 Officers and 60 Enlisted - Total 62

Manning requirements for mobilization are under development.

3. COST U/D

NAVAIR		
NAVFAC		\$ 126,033
NAVSUP		-
NAVPAC		
Identified	(Other)	\$ 82,136

4. CONSTRUCTION

Ares - .5 acres
Power - 36 KVA
Construction Time - 525 Man Hours

5. MATERIEI. (MAJOR ITEMS ONLY)

	CONTRIBUTING SYSCOM
(61 ea)	ATR
(6 ea)	AIR
(24 es)	AIR
(2 ea)	AIR
	(6 ea) (24 ea)

5. MATERIAL (MAJOR ITEMS ONLY) (CONTINUED)

Electrical Power		
60 Hz, 60kw	(4 ea)	AIR
60 Hz, 200kw	(2 ea)	AIR
400 Hz, 7.5kw	· (7 ea)	AïR
Portable Buildings		
Aircraft Support Shop	(1 ea) U/D	FAC
Head Facility	(1 ea)	FAC
Truck, & Ton Utility	(2 ea)	FAC
Truck, 21 Ton Corgo	(1 ea)	FAC
Truck, 1 Ton T4	(2 ea)	FAC
Forklift, 10 Ton	(1 ea)	SUP
Miscellaneous TBA Items		SUP

WEIGHT: Approximately 579.4 long tons

CUBE: Approximately 2328.9 measurement tons

NAVAL FACILITIES ENGINEERING COMMAND

FACILITIES

PACICITY OR GROUP	ASSEMBLY OR ECC	NORTH	(TEMPERATE)	TUTALS
211 70B	Aircraft Support Shop 40X70	OTY	WEIGHT LBS 28,279.81	CUBIC FT 1,587.04
723 20X	Head Burn Out Four Hole w/Urinal Elec Pwr Plant Dal 1-30KW w/Plwtnk	2	4,528.70 5,764.44	240.78 135.58
	Elec Distr Line 1500FT Ugnd #1	ī	649.48	9.09
	CIVIL ENGINEER SUPP AT EQU	UIPMENT (C	ESE)	
030731 058812 088002	Trk 3/4T Util Trk 5T Cargo Ml. Trlr Tk 400G SS	2 1 2	11,000.00 22,144.00 5,600.00	1,280.00 2,063.00 1,300.00

1. MISSION

This is a mobile, shore-based facility that provides Intermediate Level Maintenance Repair Capability for a nine aircraft P-3C Squadron deployed to an advance base for extended operations (granter than 50 days). If operations beyond 30 days but less than 90 days are expected at the deployment afte and adequate Supply Lines of Communications (SLOC) are available, this ABFC need not necessarily be deployed in its entirety. Only those modules (elements) herein which provide the battery shop/s, support equipment, support equipment maintenance, oxygen/nitrogen recharging and pre-positioned codes P&E IMRL equipment capabilities are required. However, if adequate SLOC are not available or if operations are planned beyond 90 days, it should be fully deployed.

This ABFC is required on a one per site basis, if more than one squadron is to be supported, early visibility is required in order than the component can be tailored upward to support the additional workload. Additional spares and repair parts, and selected support equipment and personnel will be required, especially if the additional workload is generated by an off-station squadron/detachment.

This facility consists of sixty-two 20 ft by 8 ft by 8 ft nobile vans and a rapidly erectable, portable, arch-type building to house full avionics repair capability, including PME/CAL and micro-min repair, and selected airframe/power plant repair capability, necessary maintenance control, Supply Support Center, and administrative support spaces, technical library, maintenance forms and publications, adequate rotable pool material and adequate OSI for maintenance of the facility. Selected airframe/power plant repair capabilities are:

- a. Airframes Essential hydraulic/pneumatic repair, non-destructive testing, tire disassembly/build-up, corrosion repair, welding, and sheet metal fabrication/repair. Oxygen/nitrogen will be separately provided in 400 gallon air-transportable containers with vaporization/cylinder recharging provided via a single mobile facility.
- b. Power Plants Engine repair capability includes Level III engine build-up, including replacement of turbine assemblies. QECA support includes one complete QECK to be fitted to a canned nude engine. The QECA provided in the squadron's 30 day contingency support package will become a supply asset of this component when collocated with the deployed squadron. Propeller repair capability consists of disassembly/build-up, repair of de-icer elements, dome re-seal, propeller control external leakage repair including propeller and seal plate build-up. One complete spare propeller (including propeller assembly and controls) is provided with this component. The build-up propeller provided in the squadxon's contingency support package will become an asset of this component when collocated with the deployed squadron. Two spare gear reduction assemblies are included in this component. Auxiliary Power Unit (APU) maintenance will be limited to component or end item replacement only.

Battery shop includes capabilities for storing and servicing both NICAD and lead/acid types. As adequate initial supply of space batteries of both types is included.

The component is composed of individual modules designed to provide support to specified systems/equipment and/or provide specific shop/work center support. The modules contain the mobile facilities, personnel, support equipment, ancillary equipment, and parts/materials necessary to provide Intermediate level maintenance support for the aircraft systems/equipments intended. Modularization of this component allows a phased build-up thus minimizing the necessity for massive initial transport requirements.

This component, when added to the 1-3 Squadron (Common) Support ARNC, if required, and the equadron's organic expability, will provide all necessary maintenance support for a single VP squadron operating at projected wartime flight hours.

This component is composed of 13 modules capable of specified functions in the intermediate maintenance support of P-3 aircraft systems and airborne equipments. Missions of each of the modules, their recommended assigned Unit Types Codes (UTC), number of mobile facilties, and approximate weight and cube are described as follows:

TITIE	MISSION	UTC	No. MFs	WI(LI)	CU(MI)	
Mechanical Support following capabili		9524A	14	142,4	512.0	
Tire Shop		Provides wheel and tire maintenance for alworaft and support equipment.				
Airirames	component	Provides metal and fiberglass repair, hydraulic component repair and weldi a, machine and survival equipment shops.				
Power Plant/ Propeller Shop	of power limited c	Provides gearbox/torquemeter limited maintenance of power section, auxiliary power unit (APU) limited component/end item replacement, and over/on-the-wing turbine/gearbox replacement.* *Note 2.				
Hon-Destructive Inspection (NDI)		Frovides aircraft and support equipment non-destructive inspection.				
Support Equipment/N Haintenance shops	(other che intermedia	Provides servicing and repair of support equipment (other then avionics) used by organizational and intermediate levels of maintenance of MPs and associated ancillary equipment. *Note 2				
Battery Shop Suppor following capabilit		95248	2	17.8	64.0	
•		Provides lead-acid and NICAD battery handling,				

storage, servicing and recharging.

Tool Room Support Module. Includes following capabilities -Provides administration/control of maintenance, storage/maintenance of technical data, working avace for Quality Assurance personnel, and secure storage/issue of tools and other equipment. 9524H 8.9 32.0 Liquid Oxygen/Nitrogen Support Module. 1 Includes following capabilities -Provides for generation and distribution of gaseous oxygen and nitrogen. 9524L 11 115.6 664.9 Supply Support Modules. Includes following capabilities -Provides management and compartmentalized storage of AVCAL/OSI material and upline asset and functional capabilities management information. *Note 3. 9524N Kadar/ESM/IRDS Support Modules. 3 26.7 96.0 Jucludes following capabilities. -Provides test, check and repair of radar/ESM/IRDS systems and associated equipment. 95338 26.7 96.0 COM/NAV Support Module. Includes following capabilities -Provides COM/NAV (including communications security hQ) and associated equipment test and check of repair. 8.9 95240 1 32.0 INS Support Hodule. Includes following capabilities -Provides inertial navigation systems, electrical instruments and associated equipment test, check and repair. 9524R 2 17.8 64.0 ASW Support Modules. Includes following capabilities -Provides ASW systems test, check and repair. 9524T б 53.4 192.0 PME Calibration Support Module. Includes following espabilities -Provides test equipment repair and Type IV field calibration. 9524V 53.4 192.0 ATE Support odules. Includes following capabilities -Provides test, check and repair of general avionics equipment supported by the AN/USM-449. Micro-Min Support Module. Includes 9524X 1 8.9 32.0 following capabilities -Provides test, check and repair of general

9524F

3

26.7

96.0

Productive Control, Technical Library,

avionics equipment.

Armament and Photo Repair Support Module. 9524Y 1 8.9 32.0 Includes following capabilities -

Provides test, check and repair of armament systems, photo reconnaissance and associated equipment.

- NOTE: (1) Integration Units may or may not be required when developing individual modules, depending upon deployment site facilities available. There are eight integration units assigned to each complex. Weight and cube of each unit is 8.9 LT and 32 MT, and the total weight and cube is 71.2 LT and 256 MT.
 - (2) Additionally, a separate rapidly erectable and relocatable building is included to be shared by the Power Plant/Propeller and Support Equipment Shops. The building is a rigid frame, membrane covered type structure which is currently under development. Weight and cube is included in the Power Plant and Propeller Shop Module (17.8 LT and 64.0 MT).
 - (3) Weight and cube includes 18.7 LT and 143.9 MT for items too large for storage in mobile facilities.

2. PERSONNEL:

2 Officers and 60 Enlisted - Total 62

Manning requirements for mobilization are under development.

3. COST

NAVAIR	-
NAVFAC	\$126,033
NAVSUP	_
NAVPAC	
Identified (Other)	\$ 82,136

4. CONSTRUCTION

Area Req'd - .5 acres
Power - 36 KVA
Construction Time - 525 Man Hours

5. MATERIEL (MAJOR ITEMS ONLY)

		CONTRIBUTING SYSCOM
Mobile Facilities	(62 ea)	AIR
Ancillary Equip		
Running Gear	(6 ea)	AIR
Jacks	(24 es)	AIR
Slings	(? es)	AIR

5. MATERIEL (MAJOR ITEMS ONLY) (CONTINUED)

Electrical Power		
60 Hz, 60kw	(4 ea)	AIR
60 Hz. 200kw	(2 ea)	AIR
400 Hz, 7.5kw	(7 ea)	AIR
'I' Level Support/Test Equipment	(IMRL)	AIR
Meterology/Calibration Equipment		AIR
Technical Publications		AIR
90 Day Wartime AVCAL/OSI		SUP (ASO)
30 Day CSP		
ABC WDSP		
Portable Buildings		
Aircraft Support Shor	(1 ea) U/D	FAC
Head Facility	(1 ea)	FAC
Truck, 1 Ton Utility	(2 ea)	FAC
Truck, 29 Ton Cargo	(l ea)	FAC
Truck, 13 Ton T4	(2 ea)	FAC
Forklift, 10 Ton	(1 ea)	SUP
Miscellaneous TBA Items		SUP

WEIGHT: Approximately 588.3 long tons
CUBE: Approximately 2360.9 measurement ton

NAVAL FACILITIES ENGINEERING COMMAND

FACILITIES

FACILITY OR GROUP	ASSEMBLY OR ECC	NORTH	(TEMPERATE)	TOTAL
211 70B 723 20X 811 10AE 812 30DH	Aircraft support shop 40X70 Head burn out four hole w/urinal Elec pwr plant dsl 1~30KW w/plwtnk Elec dist time 1500 ffugnd #1	QTY 1 2 1	WEIGHT L88 28,279.81 4,528.70 5,764.44 649.48	CUBIC FT 1,587.04 240.78 135.58 9.09
	CIVID ENGINEER SUPPORT EQU	TPMENT (CE	SE)	
030731 058812 088002	Trk 3/4T util Trk 5T cargo ml Trlr TK 400G ss	2 1 2	11,000.00 22,114 0 5,600 00	1,280.00 2,065.00 1,300.00

1. MISSION

H14E

Provides storage for jet fuel and aviation gasoline to refuel aircraft and aircraft refuelers with uncomtaminated fuel. The tank farm provides for 50,000 barrels of jet fuel and 3,000 barrels of aviation gasoline. It includes tanker mooring, sea loading lines, booster and delivery pumps, fuel servicing units, and both center point and over wing dispensing nozzles.

Heat is required for diesel fuel only in northern installations. In addition heaters are provided for northern installations where temperatures fall below 32 deg F. To prevent freezing of water collected in the receiving filter sumps and filter separator dispensing equipment.

One 8 inch and two 6 inch sea loading lines are provided, one for diesel fuel, one for aviation gasoline and one for jet fuel, each rated at 857 barrels per hour.

Four 300/600 GPM fuel dispensing filter-separators with both center point and over wing dispensing nozzles are provided.

The P12A Component should be provided when local familities do not afford adequate fire protection. A foam generating system is provided.

Quick disconnect couplings are provided for cross connection with the Marine Amphibious Assault Fuel Systems and Tectical Air field Dispensing System.

2. PERSONNEL 1 Officers 12 Enlisted Men Total

	OFFICERS				ENLISTED MEN			an.		
Ech	Иo	Rank	Decig	Billet	Rate	Gp	Pay Gr	PNEC	SNEC	Title
2	1	I.TJG	3100	1946						Fuel Depot
2	1				SK1	5	6			Storekeeper
2	1				SK2	5	5			Storekeeper
2	1				CMI	8	6			Const mechanic
2	2				CN	8	3			Construction
2	1				UTC	8	7	6117		Utilitiesman
È	1				UT1	8	6	6117		Utilitiesman
2	1				UTl	8	6		9561	Utilitiesman
2	2				UT2	8	5	0117		Utilitiesman
?	7				UT3	8	4	6117		Utilitiesman

3. COST

NAVAIR			War days que desperador
SPAWAR			
NAVFAC		\$1	,820,775
navsea			-
NAVSUP			Special Company of the Company of th
nsp		\$	20,290
HAVPAC			
Identified	(Other)	\$	894,131

4. CONSTRUCTION

Area required - 15 acres
Prefab building - 960 sq ft
Piers, causeways, postoons - 2,116 sq ft
Spaces requirements - Admin and offices - 480 sq ft
Operations - 480 sq ft
POL Storage - 50,000 bbl
Power required - 48 KVA
Internal roads and parking - 24,000 sq yds
Construction Time - 35,115 Man Hours

NAVAL SUPPLY SYSTEMS COMMAND

Sub-Function Codes

Rei	Description	WI	CU
10	Damage and safety control material	407	15
11	Administrative equipment and supplies	51	3
14	General equipment and supplies	1146	44
85	Fuel for heating	9900	2.55
86	Fuel for vehicles and equipment under		
	32 deg	134514	3445
87	Fuel for vehicles and equipment over		
	32 deg	126864	3248
88	POL for under 32 deg	5972	154
89	POL for over 32 dea	5032	120
99	Forms and publications	10	į

NAVAL FACILITIES ENGINEFRING COMMAND

FACILITIES

FACILITY ASSEMBLY	N	ORTH (TEMPERATE) TOTALS
OR GROUP OR ECC			
	Ó.L.Ä	WEIGHT LBS	CUBIC FT
121 10A Aircraft Direct Pueling Station	4	26,531.16	2,262.56
121 20A Aircraft Truck Fueling Facility	4	60,957.88	2,791.40
125 10A Pol Pipeline Sealouding 8 in h	1	138,834.70	5,120.60
125 10J Amphibious Assault Sub Fuel Line 6	₹ 2	227,206.30	16,365.94
125 10TF Tank Farm Detsils	I	. 00	.00
125 10W Pol Pipeline JP-5 Product	1	138,190.56	2,350.69
125 10X Fol Pipeling Diesel Product	1	48,654.70	679.17
125 10% Pol Styeline Avgos Product	1	54,214.90	760.21

NAVAL FACILITIES ENGINEERING COMMAND (CONTINUED)

FACILITIES (CONTINUED)

FACILITY OR GROUP	ASSEMBLY OR ECC	1	NORTH (TEMPERATE)	TOTALS
125 16A 125 16C 125 16E 125 16F 143 75B 218 65C 411 20A 411 30B 411 50A 811 10AA 811 10AA 812 30PA 843 10J 843 10T 843 20D 843 35A	Pumping Station Pol 6N W/One 600GPM Pumping Station Pol 8N W/One 600GPM Filter Separator Station 600 GPM Pumping Sta Pol 6N W/One 350GPM PMP Pol Operations/Smplg/Test ug Bldg Shelter WD Frame Gen Purp 18X33 PT Shelter WD Frame 12X16FT (Enclose) Aviation Gasoline Storage 3000B BBL Pol Storage 1000 BBL Fuel Storage 1000 BBL Elec Pwr Plant DSL 1-15KW W/Plwtnk Floodlight Diesel 5KW Elec Distr Line 1000PT #8 Exped Fire Protection Pipeline Tank Farm Fire Protection Pipeline Foam Gen Sys Fire Protection Pumpg Sta 500 GPM Fore Protection Reservoir Read With Draininge 1 Mile		WEIGHT LBS 26,602.00 54,652.01 81,570.32 7,988.37 40,275.67 14,800.42 24,136.45 57,014.64 30,091.55 708,706.40 4,942.28 15,200.00 160.00 79,788.77 42,114.88 14,390.67 4,136.62 44,988.00	CUBIC FT 1,233.48 2,209.20 4,134.56 263.57 1,677.89 361.32 785.85 1,258.23 737.40 12,302.55 126.48 1,992.00 20.00 1,344.76 1,217.10 509.10 173.72 1,947.00
ODI LOA	CIVIL ENGINEER SUPPORT EQ	_	•	1, 547.00
036031 088002	Trk 11 Cargo Trlr Tk 4000 SS	1	6,000.00 2,800.00	750.00 650.00
	TOOL KITS			
80013	Ki Plumbers F/4 Men Kit Tank Erection F/4 Men Kit Mech Hand Tools F/2 Men Kit Miscellaneous Tools	1 1 1	316.75 878.42 344.62 358.52	8.32 24.65 21.03 27.53
	WATERFRONT, SMALL CRAFT AND I	IARINE E	QUIPMENT	
991 23A	Barge Pontoch 4X12 W/12-1/2T Crane	1	188,007.38	13,908.68
	INITIAL OPERATIONAL S	UPPLIES		
60000	Kit Test Petroleum	1	107.36	2.08
	FERSONNEL RELACED SU	PPLIES		
67501	Kit Respirator	1	59.35	7.60
Weight -	1170 Short Tone			

Weight - 1170 Short Tone Cube: 1900 Nessurement Tons

% Containertzable: 94%

Est. Aircraft loads: 52 C141 wasds plus t C5 load

1. MISSION

Provides a hydrant-type refueling system to supplement or replace tank trucks for refueling of corrier, patrol, or helicopter aircraft. System receives fuel from a pipe line, tank truck, 55-gallon drums, or other source, stores it, filters it, and dispenses it directly to aircraft from refueling units located on a refueling apron or taxiway. Rate of refueling veries with number and type of aircraft being refueled. Maximum rate for center-point refueling is 600 gallons of jet fuel per minute for two aircraft or 300 gallons per minute for four aircraft. Overwing rate is 150 gallons per minute for each of eight hoses. System can handle jet fuel or gasoline. It contains collapsible tanks and light-weight hose for rapid installation, and can be transported in one cargo type sircraft.

2. PERSONNEL 6 Officers 6 Enlisted Men Total 6

	OFFICERS			ENLI	STED M	ŒN				
Ech	No	Renk	Desig	Billet	Rate	Gp	Pay Gr	PNEC	SNEC	Tîtle
	1				CM2	8	5			Const Mechanic
<u>.</u>	1				UTC	8	7	6117		Utilitiesman
L	1				UTl	8	6		9561	Utilitiesman
l	2				UT2	3	5	6117		Utilitiesman
l	1				UT3	8	4	6117		Utilitiesman

3. COST

NAVAIR	Marie Carlos
SPAWAR	-
NAVFAC	\$409,631
NAVSEA	-
NAVSUP	Marin dated to the foreign of selection
NSF	\$ 2,994
NAVFAC	
Identified (Other)	\$142,352

4. CONSTRUCTION

Area required - 2.5 acres Power required - 8 KVA Construction time - 348 M-Hrs

5. MATERIEL (MAJOR ITEMS)

Ready storage, collapsible tank; pumps, valves, hose and fittings Filter - separators

WEIGHT: 79 short tons

CUBE: 248 measurement tons

Z CONTAINERIZABLE: 80%

EST. AIRCRAFT LOADS: 31 C141 loads

NAVAL SUPPLY SYSTEMS COMMAND

Sub-Function Codes

Ref	Description	WI	CU
10	Damage and safety control material	138	5
	Administrative equipment and supplies	21	2
	Personnel equipment and sundries	104	8
14	General equipment and supplies	1,646	47
86	Fuel for vehicles and equipment under		
	32 deg .	10,334	267
87	Fuel for vehicles and equipment over		
	32 deg	10,334	267
88	POL for under 32 deg	9.57	25
89	POL for over 32 deg	957	25

NAVAL FACILITIES ENGINEERING COMMAND

FACILITIES

PACILITY OR GROUP	ASSEMBLY OR ECC		NORTH (TEMPERATE)	TOTALS
	• • • • • • • • • • • • • • • • • • • •	QTY	VEIGHT LBS	CUBIC FT
121 10A	Aircraft Direct Fueling Station	`5	33,163.95	2,828.20
124 30E	Aircraft Ready Fuel Stor 1/000 gal	8	6,876.88	346.80
125 10Z	Hoseline Pol	1	20,506.42	826.25
125 16G	Pumping Sta Pol W/one 1200 GPM	1	1,300.68	350.00
	Pump			
143 75A	Pol Opn/Sampling/Test Facility	1	1,504.14	115.32
811 108A	Floodlight Diesel 5KW	3	7,600.00	996.00
	TOOL KITS			
80045	Kit Auto Tools Small	1	192.20	10.01
80080	Kit Repair F/Collapsible Drums	2	80.00	1.00
81007	Kit Miscellaneous Tools	1	358.52	27.53
	INITIAL OPERATIONAL	em	PRITEC	
	THILTE OF EAST OWNE	SUF	E 3.4 45-3	
60000	Kit Test Petroleum	1	107.36	2.08

1. MISSION

The Blood Bank is a facility of the M-1-E/M-2-E medical component. As a separate facility it provides blood bank capability where none exists or augments an existing blood bank. It may also be employed as a Blood Supply Unit (BSU). The blood bank has the following capabilities:

- a. Provides organic blood collection capability of 180 units of whole blood which can be subsequently converted to packed cells.
- b. Provides monitored mechanical refrigerated storage for 500 units of whole blood or packed cells.
- c. Provides a maximum capability of crossmatching two units of blood for each of 300 parients with bulk supplies (three days of coeration).
- d. Provides monitored frozen (-80° Centigrade) storage for 500 units of frozen blood products (RBC, plasma, and platelets).

The M-11-E is a rapidly deployable, readily erected unit housed in a 3:1 ISO shelter; it contains three days supplies. All necessary equipment is shipped in the shelter. Eventually, the module will contain a resuscitation fluid production system which will produce all the cell wash solutions required by the blood bank.

Specialized utilities such as distilled water must be provided. All logistics support must be provided by the hospital or base to which the M-II-E is attached.

e. General Information. The blood bank receives patient blood samples for transfusion compatibility testing (crossmatching). The patient's blood sample is ordinarily tested for ABO and RH blood types and suitable units are selected from general blood inventory and tested for compatibility with the patient's blood sample. Alternatively, units of type 0 blood may be administered to a patient without performing a crossmatch. After testing, the compatible units of blood are stored until picked up by (issued to) the ordering clinical service for transfusion. One large refrigerator (NSN 4110-01-117-3902) will provide refrigerated storage for 500 units of liquid blood at 1°C to 6°C. One ultra-low freezer (NSN 4110-01-234-8152) provides frozen storage for red 'loo' cells, fresh frozen planma, and platelets at -80°C. A 42 $^{\circ}$ water bath (Blue Model 1140A) and four blood cell washers (NSN 6640-01-235-6131) are also provided for thewing and washing frozen products. Blood products will normally be supplied to the blood bank from a blood transshipment center (BTC) or a BSU (BSU may itself be a M-11-E); blood shipments are coordinated by the area joint blood program office (AJBPO). Blood may also be provided using organic resources, which provide adaptability to draw 180 units of blood, or from an accompanying M-12-E module. Note that blood cannot be collected from within the M-11-E spaces and actual bleedings Will require the use of beds located elsewhe a. The blood bank's capability to process blood collected with organic resulties is limited to ABO, Rh. and autoagglutination control testing. Antibody screen testing is also possible

1. MISSION (CONTINUED)

if reagent red cells are available. The blood bank is not capable of performing NBsAg, RPK, HIV, ALT and Anti-HBc. A refrigerated centrifuge is provided to prepare packed red blood cells (PRBC) from whole blood when required. The centrifuge also provides capability for preparing platelet concentrate from freshly collected blood when this product is required. An administrative area is provided for management functions and record maintenance. A TAMMIS module is also located in this area for inventory, shipping and receiving functions.

2. PERSONNEL

1 Officers

9 Enlisted Men Total 10

	OI		OFFICE	FFICERS		STED MEN	
Ech	No	Rank	Desig	Billet Rate Gp	Pay Gr	PNEC SNEC	Title
	1 1	LT	2300	0866 HMC	7	8506	Med Technologist Lab Tech (Adv)
	2			HMC	6	8506	Lab Tech (Adv)
	2 4			HM2 HM3	5 4	8506 8506	Lab Tech (Adv) Lab Tech (Adv)

3. CCST

NAVFAC \$166,237 Identified (Other) \$ 18,572

4. CONSTRUCTION

Area Required - .1 Acres

ISO Shelters - 400 Sq. Ft.

Shelter crea - 3:1 ISO container, approximately 160 mg c

Power Required - 15KVA

Overhead lighting

110V service for laboratory equipment

220V mervice for refrigerated centrifuge

Emergency power for

Refrigeration equipment

Mission critical laboratory equipment

restimate: 7 amps per workstation)

Water - One sink with HW, CW and drain

HVAC - Filtered air for dust control to a level consistent with

laboratory testing procedures

lemperature control to a level consistent with reliable

refrigeration equipment functioning and temperature sensitiva test

procedures, estimated range 4 65F to + 80F

Construction Time - 263 Man Hours

5. MATERIEL (MAJOR ITEMS)

NAVAL MEDICAL COMMAND

Sub-Function Code

Ref	Medical Assemblies	r/r	QTY	WI	CU
42	Code D-304 Laboratory Blood Bank	EA	1	26,532	2,193

NAVAL FACILITIES ENGINEERING COMMAND

FACILITIES

PACILITY OR GROUP	ASSEMBLY OR ECC		NORTH (TEMPERATE)	TOTALS
O. (STARTS OF SECTION	OTY	WEIGHT LBS	CUBIC FT
510 10MS	Blood Sank (Expeditionary)	1	26,532.01	2,192.95
811 10TA	Electric Power Plant GED 5KW	1	610.30	21.30
811 60A	Generator Conversion Kit (Standby)	1	30.85	1.63
812 12PA	Transformer Station 15 KVA Pad Mtg	1	537.35	22.65
812 30PE	Elec Distr Line 1000FT #6	1	268.82	10.00
812 30PR	Cable Assy (ISO) 60A and 30A	1	478.75	14.46
832 10AF	Sanitary Sewer 300 Ft 2N PVC	1	1,024.00	35.70
	CIVIL ENGINEER SUPPORT EQU	IPMEN	T (CESE)	
030731	Trk 3/4T Util	4	22,000.00	2,560.00

F688U

1. MISSION

The Casualty Staging Unit serves as a temporary holding area for 25 patients awaiting evacuation/transfer to another facility either intra or inter theatre. Clinical capability is limited merely to continuing the medical treatment prescribed for the patient during movement to the next facility. It is usually located in the vicinity of or as an adjunct to a hospital. The activity to which the unit is attached must provide all required logistic support.

The Casualty Staging Unit receives patients from medical treatment facilities by means of the user service's transportation. Patients are held no longer than four hours. Medications must accompany the patient from the user treatment facility. Routine processing capability for the unit is one hundred patients per day with maximum surge capability to one hundred fifty patients per day. The unit contains five days of supplies when deployed and is both air and ground mobile.

2. PERSONNEL

0И	RANK/ RATE	DESIG	NORC/ NEC	TITLE
1	LT	2100	0108	Family Practitioner
1	LCDR	2900	0940	Charge Nurse
2	LCDR/LT	2900	0944	Primary Care Nurse
8	нм3/ни	HM	0000	General Service HM
7	HM1/HM3	MII	8404	Field Medical Service Technician
2	HMC	HM	8425	Advanced (IDT) Technician
1	HM2	HM	8482	Pharmacy Technician

MC=1; NC=0; HM=18

3. COST

NAVFAC: \$554,114

NAVFAC

Identified (Other) \$ 33,123

4. CONSTRUCTION

Area Required - .1 acre

Tents - 936 sq 1t

Power - 28 KVA

Construction Time - 161 Man Hours

5. MATERIAL (MAJOR ITEMS)

NAVAL FACILITIES ENGINEERING COMMAND

FACILITIES

PACILITY OR GROUP	ASSEMBLY OR ECC	N	ORTH (TEMPERATE)	TOTALS
£10 1011		QTY	WEIGHT LBS	CUBIC FT
510 10NJ	Casualty staging unit tent 18X52ft	.3	5,290.02	421.29
811 1CBB	Electric power plant diesel 2-5KW	1	2.395.20	126.11
812 30PK	Distr ctr port 208/120V 30A 3TH	1	185.30	10.30
	CIVIL ENGINEER SUPPORT EQUI	PMENT	(CESE)	
006501	Bus FC AMB conv	4	104,000.00	12,000.00
030731	Trk 3/4T util	4	22,000.00	2,560.00
036031	Trk 11/4T cargo	1	6,000.00	750.00
036131	Ambulance heavy	6	44,850.00	6,318.00

1. MISSION

s component consists of construction equipment and materials designed ir bomb damage to airfield pavements. The component includes a War Damage Repair Kit for Air field Pavements, which is an ABFC Facility containing sufficient material for the repair of mine bomb craters. For the tender of more than nine craters the planner may order out additional War Damage Repair Kit Facilities for Atrfield Pavement Repair. The operation planner should include on the force list, one P36 for each airfield to be repaired.

Manpower way be provided by the Naval Construction Force and/or station personnel. The operation plunner may include on the force list a Naval Mobile Construction Battalion Air Detachment, Personnel Only, Unit Type Code 839DR for an Active Unit or Unit Type Code 9837D for a Reserve Unit.

2. PERSONNEL--NONE

3. COST

NAVAIR	\$ 233,300
SPAWAR	•
NAVFAC	\$6,205,692
NAVSEA	
NAVSUP	\$ 58,000
NSF	\$ 14,000
NAVFAC	
(Identified Other)	\$ 305,548

4. CONSTRUCTION

Construction Time - 335 man hours

5. MATERIAL (Major Items)

Tractors, scoop loaders, iump trucks, road graders, rotary sweepers, pheumatic drills, paving breaker, water trucks, motorized rollers, trailer floodlights, compressor, AM2 mating, connectors, towing bars and repair tool kit.

- 36 Sets AM2 mating (5680-00-191-3665)
- 4 RRR Patch Kit (5680-00-089-5391), AM2 tools and accessories
- 14 sets portable radio equipment w/accessories
- 4 Forklift, 6000lbs.
 - CBR Individual protective
 - CBR Group gear

5. MATERIEL (MAJOR ITEMS)(CONTINUED)

CXSE

- 2 jeeps, utility 4x4 from page 1
- 9 trucks, cargo 2-1/2 T 6x6
- 9 trucks, tractor 5 T 6x6
- 18 trucks, dump 10 CY 6x4
- 1 truck, tend, fuel servicing 1200 gal.
- 2 semi trailers, stake 201
- 2 Dolly, trailer 8T
- 4 water distributors, 2000 gal.
- 9 compressor units, rotary, 750 CFM
- 4 drills, preumatic, crawler mtd.
- 5 graders, road DED, 6x4
- 9 lolders, scoop type, full trkd., DED 2-1/2 CY
- 2 loaders, scoop type, wheeled, 4x4 DED 5 CY
- 9 roller, motorized, compactor, vib.
- 9 tractors, full tracked
- 9 tractors wheeled 4x2
- 7 floodlight sets, trlr mtd.
- 2 welding machines, trlr mtd.
- 5 pump units, whl-mtd, 400 GPM
- 2 sweepers, magnet tractor mtd.

Tool Kits

18 tampers, vib port rammer set, GED

NAVAL SUPPLY SYSTEMS COMMAND

Sub-Function Codes

	Ref			
91	materials handling equipment	(provided by SPCC)	WI	CÜ
	Gas forklift 6000 lbs (4 ea)	•	41,200	1832

NAVAL FACILITIES ENGINEERING COMMAND

FACILITIES

FACILITY ASSEMBLY OR CROUP OR ECC	NOF	RTH (TEMPERATE)	TOTALS
	QTY	WEIGHT LBS	CUBIC FT
111 01WD War Damage Repair Kit for Airfields	4	117,060.00	7,075.28
111 02WD War Damag Repair Kit For Airfields	5	.00	.00
136 00WD War Damage Repair Kit F/Airfield	1	8,888.50	456.84

CIVIL ENGINEER SUPPORT EQUIPMENT (CESE)

FACILITY	ASSEMBLY			
OR GROUP	OR ECC		NORTH (TEMPERATE)	TOTALS
		QTY	WEIGHT LBS	CUBIC FT
030731	Trk 3/4T Util	2	11,000.00	1,280.00
064301	Trk Stake 46000GUW 6x6	6		
064512	Trk Trac 46000 GUW 6x6	9	173,340.00	13,644.00
064402	Trk Dump 6x6 46000 GUW	18	396,000.00	28,980.00
000000	Trk Tank Gen PU 6x6 46000 GUW	1	-	-
086231	Trlr Tilt Deck	9	118,800.00	14,499.00
252105	Distrib Water 46000 GUW 6x6	5	92,500.00	8,105.00
313501	Compres 250CFM	9	37,800.00	5,427.00
442001	Grader Motor	5	153,500.00	12,720.00
453031	Losder Full-Trk	9	442,503.00	17,361.00
453152	Loader Scoop WH	2	158,420.00	7,600.00
463523	Roller Vibrate	9	197,100.00	12,330.00
485022	Tractor Crawler	9	410,400.00	14,130.00
487501	Tractor Wheeled	6	69,000.00	7,194.00
511022	Floodlight Trlr	12	45,600.00	5,976.00
522021	Pump Centrifug	9	5,373.00	270.00
571021	Magnet Road Swp	2	3,000.00	572.00
	TOOL KIT	S		
80004	Kit Gas Cut and Weld W/Rod	1	159.53	17.24
82020	Wrench Set Imp Pneu 1/2DR Sckts	5	155.00	9.45
82050	Tamper Vib Port Rammer Set GED	18	4,203.00	343.80
85036	Rapid Runway Repair Tool Kit	1	2,100.86	198.74

Weight: 1350 Short Tons

Cube: 4450 Measurement Tons
Z Constainerizable: 9%
Est. Aircraft Loads: 35 C141 loads plus 9 C5 loads

APPENDIX B. SAMPLE SURVEY PACKAGE

GENERAL SURVEY INSTRUCTIONS

PRIORITIZATION OF ADVANCED BASE FUNCTIONAL COMPONENTS (ABFC)

You are the Commander of Naval Forces in a theater of operations (e.g. if OPNAV, CINCLANT, COMSERVLANT, NAVMEDCOM, etc.-- the Atlantic theater; if CINCUSNAVEUR, COMFAIRMED -- the European theater, etc.). The scenario is Base Case -- global conventional war with initial outbreak in Europe. It is now D+10, 10 days after the start of the war. You currently have the capabilities of any and all ABFCs you require to carry out your operations. You may run out of any of these. You will find descriptions of the ABFCs you are rating at enclosure (5).

The forms at enclosures (2) and (3) are two separate surveys which use different methods to elicit preferences. The specific directions for each survey are contained at the top of the survey form. DO NOT GO BACK AND CHANGE ANY OF YOUR RESPONSES!!! In addition. It is urged that, after you complete Survey 1, wait several hours or until the next day to complete Survey 2. They must be completed independently for the results to be useful. The questionnaire at enclosure (4) is your opportunity to express your opinions about the survey designs and to make explanatory comments about any of the responses you gave. Please include the completed questionnaire when you return the surveys.

If you have any questions or desire further information, contact LCDR Linda Guadalupe: autovon 878-2786, commercial (408) 649-8036; or Dr. Samuel Parry; autovon 878-2779 commercial (408) 646-2779.

SURVEY 1

EFFECT OF MORS OF ABEC ON MISSION ACCOMPLISHMENT

You are starting with the capabilities of any and all the ABFCs you require to carry out your war plans. For each ABFC listed below, determine the level of detriment to the accomplishment of your objectives that would result if you were to be denied only that particular ABFC. Place a mark in the block under the appropriate category. DO NOT CHANGE A RESPONSE ONCE YOU HAVE DECIDED ON IT AND MADE THE MARK!!! Your first response is the one that is needed for research purposes.

TITLE	ABFC CODE	N∋ EFFECT	SOME DETRIMENT	SERIOUS DETRIMENT	WAR STOPPING
Naval Station Communicat (AMCC Van)					
Cargo Handling Battalion	F1	A year (III - Mail A shallach de Mhaille an ann an ann an Aibheille an ann a			<u>Makhaning at a kingga king pahama</u> y sa si sa <u>uta</u> ng Ka
P-3C Intermediate Suppor		Programmina in groups over une prinche authorization commission in section		and the state of t	A dispublican and process or a many first pay of a paying and the dispublicant and the second dispublicant and the second dispublicant and the second dispute an
DFM & JP-5			n de la commissione de la commissión de la companya de la companya de la commissión de la commissión de la comm		
Repair	P36				
Hi Speed Fuel Mispensing System			entre en grande de la companya de l		New York State Sta
Casualty Staging Un	M16E	e e e e e e e e e e e e e e e e e e e	ing white time a material is suggested in 2.5 Most facilities in a suggest a confidence in the facilities of the suggest and t	A Berlinka demonstrate (* 1948) word (* 1945) who believe to demonstration of	to to demonstrate in a statement and a constant that have a where

TITLE	ABFC CODE	NO EFFECT	SOME DETRIMENT	SERIOUS DETRIMENT	WAR STOPPING
P-3 A/B Inter- mediate Su Activity			The control of the co		and the second s
Blood Bank	7111	Michigan - Committee & Martine and Administration in Management and Administration and Ad	NOTE I PART, ROBERT VINIVALUELLE, VILINGARIANA AND ARTHUR SEMENTAL LAPER CHAIN IN. AS	. To complete large and the complete large an	
Aviation Tank Farm (basi		and the state of t	CHARLES SERVIN STANCE / An SPANSETT COMMERCED AND	enderwooning on the law opening to be the law of the la	Mary Co. 1980 (1985) Mary 28 da 3,478,d hand (1986) (1986)
Naval Overseas Air Cargo Terminal (Secretain appealation and commercial account and an advantage	THE SCHOOL SECTION AND ASSESSMENT OF THE SECTION SECTI	dia russi, espera di Alifanda di Bandari del Goste e espera del gardo e espera del gardo e espera del gardo e	N. N. S.

SURVEY 2

PAIRWISE COMPARISONS: RELATIVE EFFECT OF LCSS OF ABFC ON MISSION ACCOMPLISHMENT

You are asked to compare two ABFCs to each other, with regard to which of the two would cause more detriment to the mission if both were lost. In addition, you will give your comparison a number to designate how much more detriment the one you chose would cause. The following are descriptions of the possible "intensity values" you may choose for each pair.

INTENS VALUE	ry DEFINITION	EXPLANATION
	Equal importance	Loss of these two ABFCs would cause equal detriment to the mission. Both are needed equally.
3	Weak importance of one over the other	Your experience and judgment tell you that one ABFC is moderately needed more than the other.
5	Essent al or strong importance	Experience and judgment tell you that one ABFC is strongly needed more than the other.
7	Very strong importance	Cre ABFC is very strongly needed more than the coher; its dominance is obvious from experience.
9	Absoluta importance	Your unqualified opinion is that there is the highest order of need for one ABFC over the other.
2,4,6,8	Intermediate values between two adjacent intensities	When you must compromise

Now you are ready to complete Survey 2. Please compare each of the following pairs of ABFCs, a pair at a time, independently of any of the other pairs. Choose the letter, X or Y, which corresponds to the ABFC in that pair which would cause the most detriment to the accomplishment of your objectives if both were denied you. Then select one of the "intensity values" described above to show the extent of the comparison. (If you feel that both would cause equal detriment to the mission, write both the letters: "X and Y", and place a "1" in the column marked Intensity Value.) You are reminded: DO NOT CHANGE A RESPONSE ONCE YOU HAVE MARKED IT DOWN!!!

If both X and Y

x	Y	were lost, more detriment would by caused by the loss of:	Intensity value
AMCC VAN	P3-C INT. SUPPORT ACT.		
CARGO HAND- LING BATT.	AVIATION TANK FARM		
PU-A/B INT. SUPPORT ACT.	BLOOD BANK		
CASUALTY STAGING UNIT	P3-C INT. SUPPORT ACT.		
RAFID RUNWAY REPAIR	TANK FARM	THE RESIDENCE OF THE PARTY OF T	Andreasymphotologicals in approximate the second of the se
BLOOD BANK	RAPID RUNWAY REPAIR		
TANK FARM	CARGO HANDLING BATT.	and the second s	en 1800 bet en alle e <mark>n en en en e</mark> n en

CASUALTY STAGING UNIT

Y

TANK FARM

P3-A/B INT.

SUPPORT ACT.

X

P3-A/B INT. SUPPORT ACT.

P3-A/B INT.

CARGO HANDLING

BLOOD BANK

AMCC VAN

RAPID RUNWAY REPAIR

AVIATION TANK

FARM

CARGO HAND-LING BATT.

P3-C INT. SUPPORT ACT.

P3-A/B INT.

AMCC VAN

SUPPORT ACT.

AMCC VAN CARGO HANDLING

BATT.

NOAC

RAPID RUNWAY REPAIR

TANK FARM

CASUALTY STAGING UNIT

HI SPEED FUEL DISP. SYSTEM

AVIATION TANK FARM

CARGO HAND-LING BATT.

NOAC

AMCC VAN

CASUALTY STAGING UNIT

AVIATION TANK

BLOOD BANK

FARM

P3-C INT.

AMAT MOITAL A

SUPPORT ACT.

FARM

RAPID RUNWAY

HI SPLED FUEL

REPAIR

DISP. SYSTEM

Mor	e de	etr	cime	ent
wou	ild !	be⊢	cat	ised
ру	the	J.c	ss	of:

Intensity value

Y

x

ELOOD BANK	NOAC	
P3-C INT.	HI SPEED FUEL	
	DISP. SYSTEM	
SCITORI ACI.	D131, 01011111	
CASUALTY	BLOOD BANK	
STAGING UNIT		
D11102110 01111		
AMCC VAN	HI SPEED FUEL	
	DISP. SYSTEM	
CASUALTY	RAPID RUNWAY	
STAGING UNIT	REPAIR	
RAPID RUNWAY	AMCC VAN	
REPAIR	14.00 1111	
KLIAIK		
P3-A/B INT.	NOAC	
SUPPORT ACT.		
RAPID RUNWAY	P3-C INT. T.	
د مين داد د د د د د د د د د د د د د د د د د		
HI SPEED FUEL	CARGO HANDLING	
DISP. SYSTEM	BATT.	
BLOOD BANK	P3-C INT.	
BLOOD BANK		
	SUPPORT ACT.	
NOAC	P3-C INT.	
	SUPPORT ACT.	
	JOIT ON THEIT,	
P3-A/B INT.	RAPID RUNWAY	
SUPPORT ACT.	REPAIR	
NOAC	AVIATION TANK	
	FARM	
P-3C INT.	TANK FARM	
SUPPORT ACT.		
AMCC VAN	NOAC	ANAII Amenda (material de mais anti-
ZM MOCH VEHIC	none	
P3-A/B INT.	P3-C INT.	
SUPPORT ACT.	SUPPORT ACT.	
HI SPEED FUEL	P3-A/B INT	· · · · · · · · · · · · · · · · · · ·
DISP. SYSTEM	SUPPORT ACT.	

X	A	by the	e loss of:	value
CASUALTY	CARGO HANDLING	na. 1 v mp. Tit in en erryt 20 mingegrücklichen mande Grap geführt der	Administrative for engagement of testine recognitive of processing and distinct and other first 1 state 1 to engage	on , water the six of the statement of the experience and project the experience of
STAGING UNIT	BATT.			
AMCC VAN	TANK FARM	· · · · · · · · · · · · · · · · · · ·	Artena area delecta a must cap of Artena administra a magazina de ampagia music	
TANK FARM	NOAC		aller jakkindh Arris ja kil Mildler delst Bi-Allian Hebra Jahl H. Kili prosent ermengen en a pasa-sa	The state of the s
NOAC	CASUALTY STAGING UNIT	nateralista, jakon distala, sali Maraudi Padila (1984) dili delli		
HI SPEED FUEL DISP. SYSTEM	NOAC	hadan Adai Laddellik yirad dari Albandallik dalah 1 - Pila Pandel	ar (an agus a agus ar agus ar an an an agus agus an an an an agus an agus agus agus agus agus agus agus agus	
CARGO HAND- LING BATT.	BLOOD BANK	n mark he mand		
AVIATION TANK FARM	AMCC VAN	and the second s		
HI SPEED FUEL DISP. SYSTEM	TANK FARM			
CASUALTY STAGING UNIT	HI SPEED FUEL DISP. SYSTEM			1 00 1100000000000000000000000000000000
AVIATION TANK FARM	P3-A/B INT. SUPPORT ACT.	agir Miching, gin-Polity, qualificate quantitive, — miching quin		
BLOOD BANK	HI SPEED FUEL DISP. SYSTEM	ndel and de grand fill all any alle and any and the grand or any in a de		
TANK FARM	AVIATION TANK FARM			
RAPID RUNWAY REPAIR	CARGO HANDLING BATT.	and the second of the second o		
AVIATION TANK FARM	CASUALTY STAGING UNIT	dati dir Ana bash salaman a	and again. While have proved to the grant design and the grant design as the grant des	
BLOOD BANK	TANK FARM	i kan kilikila aya da dalah sali samalika da kilikila da s	tid dasa marekatasan , paj aminin pila andra ^a ndramiti, , , , , , , , , , , , , , , , , , ,	montani din ingga kanamanani ya zanin kanama nawanikanik

RATER QUESTIONNAIRE

1. DID YOU HAVE ANY DIFFICULTY UNDERSTANDING THE SCENARIOR PRESENTED? IF SO, PLEASE COMMENT:
WOULD YOU HAVE PREFERRED THAT THE SITUATION BE DESCRIBED OF THE STRUCTURE
2. DID YOU HAVE ANY DIFFICULTY UNDERSTANDING THE INSTRUCTION FOR GIVING RESPONSES? IF SO, EXPLAIN:
3. THE TWO SURVEYS ARE VERY DIFFERENT WITH REGARD TO DESIGN DID YOU FEEL MORE COMFORTABLE RESPONDING TO ONE THAN THE OTHER?IF SO, WHICH ONE AND WHY?
DID ONE METHOD SEEM MORE REALISTIC FOR RATING THE VALUE OF ABFCs? IF YES, WHICH ONE AND WHY?
4. USE THIS SPACE AND THE OTHER SIDE OF THIS SHEET FOR OTHER COMMENTS, INCLUDING THOSE YOU WISH TO MAKE REGARDING ANY OF YOUR SURVEY RESPONSES:

APPENDIX C. PROGRAMS DEVELOPED FOR THESIS

NORMALIZATION OF CUMULATIVE PREQUENCIES [Ref. 6: pp.87-88]

```
V NORM: MIN: NOR: FOWAY; GRAY; S: AA; F: AAI: II
                                  D+'INPUT IND CUMULATIVE FREQUENCIES'
      [1]
                                  D+'INSURE THAT THERE ARE NO VALUES OF'
     [2]
     [E]
                                  D+^{\circ}ZERO (0) OF OF ONE (1)'
     [4]
                                 M2W+D
      [5]
                                 TOR+NOUAN MIX
     [6]
                                 S+pXIX
      [7]
                                 EONAV+(+/NOR)+(S[2])
     [8]
                                 EONAV+(S[1].1)pEONAV
     [9]
                                 COLAV+(+ \neq NOR)+(S[1])
                             GRAV \leftarrow (+/(+/NOR)) \div ((S[1]) \times (S[2]))
     [10]
        11]
                                 D+'NORMALIZED VALUES
                                                                                                                                                                                        ROW AVERACE!
                                 [12]
     [13]
                                 DANOR ROWAY
                                 --! CCLUMN AVERAGES !
    * 1 Li --
    -15-
    -15-
                                 --COLAV
    -17- -- GRAND AVERAGE'
    -18-
                                 -- GRAV
    -19-
    -20- AAI-S-0
                             II-0
    -21-
   -22- L2:XI-YI+1
   -23- AA-(NOB-; (II)--, ROWAY)*2
   -24-
                            AAI-:II:-AA
  -25--(II< S-2-)/L2
   -26- AAI-(S)-AAI
   -27- AAI-+/AAI
  -28-B-+/((COLAV-GRAV)*2)
  -29- SQR-(5-AAI)*0.5
  -50-SQR-((S-1-).1)-SQR
 -SI- SSI-GRAV-(ROWAV-SQR)
  -32 - AAI - (S-1-,1) - AAI
 -33- GRAV- (S-1-,1)-GRAV
 -34- -- B
 -36- --B
 -37- -- AII
 tamanaman and the same than the same of th
 -39- --AAI
 -40- -- SCALE VALUES = GRAND AVERAGE - (ROW AVERAGE-(B-AI)*.5)*
-41-
-42- -- SSI. GRAV, ROWAV, SQR
-43- -- COLUMN AVERAGES
-54-
                            the second control of 
-55- -- COLAV
```

```
NORMAL TABLE LOOK-UP (DEVELOPED AT NPS) [REF. 6: PP. 87-88]
       V Z+NQUAN P:A:B:C:D
[1]
       →((+/(A←(P≤C)∨(F≥1)))>C)/L1
[2]
       C+ 2.515517 0.802853 0.010328
       D+ 1.432788 C.183269 0.001308
[3]
[4]
       P+((A+(P\leq 0.5))\times P)+((P>0.5)\times (1-P))
[5]
       \mathcal{B}+(\mathcal{C}P*^2)*0.5
       Z \leftarrow ((2 \times ...) - 1) \times -F - ((5 \circ ... \circ 1 \circ 2) + ... \times C) + (1 + ((6 \circ ... \circ 1 \circ 2) + ... \times D))
[6]
[7]
[8]
      L1: G - THERE IS NO QUANTILE FOR P = '. $A/P
       V
    DETERMINATION OF CUMULATIVE FREQUENCIES [REF. 6: PP. 87-88]
       V JUDGES: D:N:SHAPE: FREQ: CUNFREQ
       D+ INPUT THE RAW DATA FOIRTS !
[1]
       D+'THE NUMBER OF OBSERVALIONS'
[2]
       G+'IN EACH ROW MUST BE THE SAME!
[3]
[4]
       D \leftarrow \Box
[5]
       N++/D
[6]
       SHAPE+pD
[7]
      N+N[1]
[8]
       FREQ+D[::(SHAPE[2])] +N
       DAIRELATIVE FREQUENCY!
[9]
[10]
[11]
       D+FEEQ
      D41 1
[12]
[13]
       CUMFREQ ++ \FREQ
[14]
      D+'CUMULATIVE FREQUENCY'
       [15]
       E+CUMFREQ ...
[18]
```

SCALE VALUE COMPUTATIONS FROM PAIRWISE COMPARISONS

```
* DECLARE VARIABLES
         INTEGER P, Q, R
PARAMETER (P=11,Q=46,R=23)
INTEGER I, J, L, ARRAY(Q), C1, C2, T
         REAL FIRST, SECOND, THIRD, FOURTH, RAN(P,P,2,R), RAN2(P,P,2,R),
        1A(P,P,R), AP(P,P,R), AB(P,P), ABP(P,P), NORM(P,P), W(P,P), S(P), SP(P)
         CHARACTER*16 ABFC(P)
         DATA RAW, RAW2/5566*0,5566*0/, FIRST, SECOND, THIRD, FOURTH/0,0,0,0/
         CALL EXCMS ('FILEDEF OI DISK NAMEABEC DATA A1 (LRECL 80')
CALL EXCMS ('FILEDEF O2 DISK ABEC DATA A1 (LRECL 128')
CALL EXCMS ('FILEDEF O3 DISK ABECREP LISTING A1 (LRECL 80')
   READ NAMES INTO ABFC ARRAY
DO 3 I=1,P
              READ (01,4) ABFC(I)
4
              FORMAT (A16)
         CONTINUE
* READ DATA INTO BOTH RAW ARRAYS
100 READ (02,10,END=200) C1,C2,ARRAY
10
              FORMAT (2(13),46(12))
   TRANSFORM TO 100 POINT SCALE TO CREATE ARRAY RAWL FOR CONSTANT SUM METHOD AND ADD RECIPROCALS TO CREATE ARRAY RAW2 FOR AHP METHOD
         T = 0
         DO 15 I = 1, Q, 2
              T=T+1
                  IF (ARRAY(I) .GT. 9) THEN
    PRINT *, I,'ERROR9'
ELSE IF (ARRAY(I+1) .GT.9) THEN
    PRINT *, I+1,'ERROR9'
                  ELSE IF (ARRAY(I) .GT. 0) THEN
                      FIRST=(ARRAY(I)*100)/(ARRAY(I)+I)
                      SECOND=100-FIRST
                      THIRD= ARRAY(I)
                      FOURTH=1.0/(ARRAY(I))
                  ELSE IF (ARRAY(I+1) .GT. 0) THEN
                        ECOND=(ARRAY(I+1)*100)/(ARRAY(I+1)+1)
                      FIRST=100-SECOND
FOURTH=APNAY(I+1)
                      THIRD=1.0/(ARRAY(I+1))
                      PRINT *, I,I+1, 'ERRORUS'
                  ENDIF
* PLACE VALUES FOR COMPARISONS OF PAIRS NOT COMPARED IN OPPOSITE ORDER
   (THAT IS, PLACE THE CROSS-DIAGONAL VALUES INTO THE MATRIX)

IF (C1 .GT. C2) THEN

RAN(C2,C1,2,T)=FIRST
                      RAW(C2,C1,1,T)=SECOND
RAW2(C2,C1,2,T)=THIRD
                 RAWZ(C2,C1,1,T)=FOURTH
ELSE IF (C2,GT,C1) THEN
RAW(C1,C2,1,T)=FIRST
                      RAW(C1,C2,2,T)=SECOND
RAWC(C1,C2,1,T)=THIRD
                      RAN2(C1,C2,2,T) = FOURTH
                 ENDIF
                 FIRSTEO
                  SECOND=0
                 THIRD=0
                 FOURTH: 0
15
             CONTINUE
        GOTO 100
```

```
DO 35 L=1.R
200
            DO 40 I=1.P
            A(I,I,L)=50
           AP(I,I,L)=1
            IF_(I_EQ.P) THEN
              GO TO 40
            ELSE
              DO 45 J=I+1,P
              A(I,J,L)=RAH(I,J,2,L)
              A(J,I,L)=RAW(I,J,1,L)
AP(I,J,L)=RAW2(I,J,1,L)
AP(J,I,L)=RAW2(I,J,2,L)
              CONTINUE
45
            ENDIF
40
            CONTINUE
        CONTINUE
35
* AGGREGATE THE TWO FORMS OF MATRICES OVER ALL JUDGES, USING ARITHMETIC * MEAN FOR CONSTANT SUM METHOD (ONE AB MATRIX) AND GEOMETRIC MEAN FOR
    AHP METHOD (ONE AB-PRIME MATRIX)
        DO 50 I=1,P
DO 55 J=1,P
           AB(I,J)=0
            ABP(I,J)=1
               DO 60 L=1,R
               AB(1,J)=AB(1,J)+A(1,J,L)
               ABP(I,J) = ABF(I,J) \times AP(I,J,L)
60
               CONTINUE
               AB(I,J)=(AB(I,J)/R)
               ABP(I,J)=(ABP(I,J))**(1.0/R)
55
           CONTINUE
50
       CONTINUE
¥
 COMPUTE THE W MATRIX FOR CONSTANT SUM METHOD
        DO 65 I=1,P
DO 70 J=1,P
           W(I,J)=AB(I,J)/AB(J,I)
70
           CONTINUE
65
       CONTINUE
  NORMALIZE THE AB-PRIME MATRIX FOR THE AHP METHOD DO 75 J=1,P ^{\circ}
           DENOM = 0
           DO 80 I=1,P
               DENOM = DENOM + ABP(I,J)
           CONTINUE
80
           DO 85 I=1,P
NORM(I,J)=ABP(I,J)/DENOM
8.5
           CONTINUE
75
       CONTINUE
* COMPUTE THE SCALE VALUES FOR THE CONSTANT SUM METHOD, S(J)
       DO 90 J=1,P
       S(J)=1
           DO 95 I=1,P
           ร์้(ับว์ะิร(ับวิหิพ(I,ป)
           CONTINUE
95
       CONTINUE
90
       DO 105 I=1,P
5(I)=5(1)**(1.0/P)
105
       CONTINUE
```

```
COMPUTE THE SCALE VALUES FOR THE AHP METHOD, SP(I)
       DO 110 I=1,P
         SP(1)=0
          DO 115 J=1,P
          SP(I)=NORM(I,J)+SP(I)
115
          CONTINUE
          SP(I)=(SP(I))/P
110
       CONTINUE
* WRITE CONSTANT SUM METHOD ARRAYS TO FILE
       WRITE(3, *)
       WRITE(3,*) 'A MATRICES'
       DO 120 L=1,R
          DO 125 I=1,P
             WRITE(3,140) (A(I,J,L),J=1,P)
125
          CONTINUE
       WRITE (03,*)
120
       CONTINUE
       WRITE(3,*) 'AB MATRIX'
       DO 130 I=1,P
WRITE(3,140) (AB(I,J), J=1,P)
130
       CONTINUE
       WRITE(3,*)
       WRITE(3,*) 'W MATRIX'
DO 135 I=1,P
          WRITE(3,140) (N(I,J), J=1,P)
135
       CONTINUE
140
       FORMAT (11(F6.2))
* WRITE THE AHP METHOD ARRAYS TO FILE
      WRITE(3,300)
300
      FORMAT (/,80(1-1)/)
      WRITE(3,*) 'A-PRIME MATRICES'
       DO 145 L=1,R
          DO 150 I=1,P
          WRITE(3,140) (AP(I,J,L),J=1,P)
150
          CONTINUE
      HRITE(3, *)
145
      CONTINUE
      WRITE(3.%) 'AGGREGATED AB-PRIME MATRIX'
DO 155 1 1,P
          WRITE(3,140) (ABP(I,J), 'J=1,P)
      CONTINUE
155
      HRITE(3, *)
      NRITE(3,*) *NORMALIZED AGGREGATED AB-PRIME MATRIX*
DO 160 I=1,P
          WRITE(3,140) (NORM(I,J), J=1,P)
160
      CONTINUE
      MRITE(3,*)
      WRITE(3,300)
      WRITE(3,*) *ABFC NO. DO 165 I=1,P
                                    NAME
                                                     S (CONSUM)
                                                                      S (AHP)
          WRITE(3,400) I, ABFC(1), S(1), SP(1)
400
          FORMAT (/3X,12,6%,A16,3%,F7.3,8%,F8.4)
      CONTINUE
165
      STOP
      END
```

APPENDIX D. STEP-BY-STEP APPLICATIONS

Constructing Interval Scales From Categorical Judgments

Step 1 RAW DATA:

			LEVE	L OF DET	RIMENT
ABFC #	ABFC NAME	NQ	<u>SOME</u>	SERIOUS	WARSTOPPING
1	AMCC Vari	1	10	10	2
2	Cargo Handling Bat.	0	7	11	5
3	P-3C Int. Supp. Fac.	5	7	10	1
4	Tank Farm (med.)	2	9	12	0
5	Rapid Runway Repair	0	5	10	8
6	Hi Speed Fuel Disp.	3	13	6	1
7	Casualty Staging Unit	5	13	5	0
8	P-3A/B Int. Sup. Fac.	5	10	8	0
9	Blood Bank	6	12	5	0
10	Aviation Tank Farm	2	8	11	2
11	Nav O'seas Air Cargo	2	7	14	0

Step 2 GROUPING MATRICES: The matrices were grouped based on removal of columns with values <0.02 and >0.98.

4 7 8 9	GRPAB	0.2173913043 0 0.2173913043 0 0.2608695652 0	.4782608696 .7826086957 .652173913 .7826086957 .3913043478	
1 3 6 10	GRPABC	0.2173913043 0 0.1304347826 0	.4782608696 .5217391304 .6956521739 .4347826087	0.9150434783 0.9565217391 0.9565217391 0.9130434783
2 5	GRPBC	0.3043478261 0.7826 0.2173913043 0.6521	086957	0.5130434763

The remainder of the steps was performed for each group. GROUP AB:


```
0.3790166332
0.329938394
0.1120473742
0.3946279417
    0.6570099831
   COLUMN. AVERAGES
 0.984380637 0.324503849
 GROUP ABC:
 NORMALIZED VALUES
 1.712054734
-0.7808184192
-1.124405025
-1.359962536
                          -0.05437545303
0.05437545303
-0.51153131
-0.1638765529
                                                    1.359962536
1.712054734
1.712054734
1.359962536
 ROW AVERAGES
  0.135489217
0.328537256
0.3663936731
0.05462551764
 GRAND AVERAGE
 0.1262040486
 SCALE VALUES OF INSTANCES
  -0.2487367588
-0.2338513763
-0.2316426674
    0.181924521
  COLUMN AVERACES
1.244310179 0.08691368928 1.536008635
GROUP BC:
NORNALIZED VALUES
   0.51153131
0.7808194192
                       0.7808184192
0.3907534547
ROW AVERAGES
 -0.1346435546
0.1950324823
GRAND AVERAGE
0.03019446384
SCALE VALUES OF INSTANCES
 0.1585463934
0.1748910102
 COLUMN AVERAGES
T0.6461748646 0.5857859369
```

SCALE VALUES OF INSTANCES

SCALE EQUALIZATION: By transforming the scales for groups Al and BC so that the upper bounds of their categories were the same as those for Group ABC, the following final scale values for each ABFC were obtained:

Rapid Runway Repair	1.0527
Cargo Handling Battalion	0.6605
Naval Overseas Air Cargo Terminal	0.4251
Naval Station Communication (AMCC Van)	0.2487
Aviation Tank Farm	0.1819
Tank Farm (medium, DFM & JP-5)	0.1424
High Speed Fuel Dispensing System	-0.2316
P-3C Intermediate Support Facility	-0.2339
P-3A/B Intermediate Support Facility	-0.3571
Casualty Staging Unit	-0.5787
Blood Bank	-0.6445

The Constant Sum Method

					A	BF	C #				
RAW DATA:	1	2	3	4	5	6	7	8	9	10	11
(judge_#1)	,										
1	1	9	1	3	5	1	3		9	1	3
2]										
3	1	9		3	5	1	5	1	7	3	3
A 4	1	9			5	1	5		5		
B 5	1	7					3		š		
F 6	1	9	1	1	5		3	3	7	3	1
C 7	-	9	_	-	_		ĭ	•	3	_	
8	3	9	1	3	3	1	3		7	3	3
# 9	`	7	•		0	•	O		•	9	J
10	lı	9		5	5		5		7		3
11	1	ă		3	5		3		7		J
1.1	1	9		3	3	ı	3		1		

A MATRIX (judge #1):

10.00 50.00 25.00 17.00 50.00 25.00 75.00 17.00	50.00 90.00 90.00 87.00 90.00 90.00 90.00 87.00	10.00 50.00 25.00 17.00 50.00 17.00 50.00 13.00	10.00 75.00 50.00 17.00 50.00 17.00 75.00 17.00	13.00 83.00 83.00 50.00 83.00 25.00 75.00 25.00	10.00 50.00 50.00 17.00 1.00 1.00 1.00	75.00 10.00 83.00 75.00 75.00 75.00 75.00 83.00	10.00 50.00 25.00 25.00 50.00 25.00 50.00 13.00	13.00 87.00 83.00 75.00 87.00 75.00 87.00 50.00	10.00 75.00 17.00 17.00 75.00 17.00 75.00 13.00	10.00 75.00 25.00 17.00 50.00 25.00 75.00 13.00
50.00	90.00	25.00	83.00	83.00	25.00	83.00 75.00	25.00	87.00	50.00	75.00

AB MATRIX:

50.00	56.09	40.91	42.52	60.13	41.61	35.78	40.74	36.26	43.65	42.26
43.91	50.00	47.00	30.87	62.09	31.09	21.43	40.04	23.70	39.35	33.17
59,09	53.00	50.00	54.04	62.91	39.09	30.83	38.65	33.00	50.78	42.30
57.48	69.13	45.96	50.00	65.30	44.26	37.04	40.04	37.57	50.74	47.26
39.87	37.91	37.09	31.70	50.00	27.13	24.61	36.70	27.35	30.96	37.17
58.37	68 91	60.91	55.74	72.87	50.00	38.30	50.48	35.30	60.13	55.35
64.22	78.57	69.17	62.96	75.39	61.70	50.00	63.09	47.26	68.30	64.04
59.25	59.96	61.35	59.90	63.30	49.52	36.91	50.00	57.57	59.50	47.30
63.74	70.30	67.00	62.43	72.65	64.70	52.74	62.43	50.00	70.87	64.26
56.35	60.65	49.22	49.26	66.04	39.87	31.70	40.70	29.13	50.00	49.57
57.74	66.83	57.70	52.74	62.83	44.65	35.96	52.70	35.74	50.43	50.00

W MATRIX:

1.00 0.78 1.44 1.35 0.66 1.40 1.79 1.45	1.28 1.00 1.13 2.24 0.61 2.22 3.67 1.50 3.22	0.69 0.89 1.00 0.85 0.59 1.56 2.24 1.59 2.03	0.74 0.45 1.18 1.00 0.46 1.26 1.70 1.50 1.66	2.66	0.71 0.45 0.64 0.79 6.37 J.00 1.61 0.98 1.85	0.56 0.27 0.45 0.59 0.33 0.62 1.00 0.59 1.12	0.69 0.67 0.63 0.67 0.58 1.02 1.71 1.00 1.66	0.57 0.31 0.49 0.60 0.38 0.55 0.60 0.60 1.00	0.77 0.65 1.03 1.03 0.51 1.51 2.16 1.46 2.3	0.3 0.9 0.59 1.24 1.78 0.90 1.80
1.76 1.29 1.37	1.54 2.01	0.97 1.36	$0.97 \\ 1.12$	1.69	0.66	0.46 0.56	0.69	0.41	1.00 1.02	0,98

SCALE VALUES:

Rapid Runway Repair	1.893
Cargo Handling Battalion	1.646
Naval Station Communication (AMCC Van)	1.249
P-3C Intermediate Support Facility	1.148
Aviation Tank Farm	1.112
Tank Farm (medium, DFM & JP-5)	1.004
Naval Overseas Air Cargo Terminal	0.938
P-3A/B Intermediate Support Facility	0.881
High Speed Fuel Dispensing System	0.807
Casualty Staging Unit	0.549
Blood Bank	0.548

The Analytical Hierarchy Process

RAW DATA: Same as for the Constant Sum Method

A-PRIME MATRIX: (judge #1)

9.00 1.00 3.00 5.00 1.00 3.00 0.23 5.00 1.00 3.00	0.11 0.11 0.14 0.11 0.11 0.11 0.14 0.11	1.00 3.00 5.00 1.00 5.00 1.00 7.00 3.00 3.00	0.33 1.00 5.00 1.00 5.00 0.33 5.00 0.20	0.20 0.20 1.00 0.20 3.00 0.33 3.00 0.20	9.00 1.00 1.00 5.00 1.00 3.00 1.00 7.00 3.00	9.00 0.20 0.33 0.33 1.00 0.33 3.00 0.20	9.00 1.00 3.00 1.00 3.00 1.00 7.00 3.00	7.00 0.14 0.20 0.33 0.14 0.33 0.14 1.00 0.14	9.00 0.33 5.00 0.33 5.00 0.33 7.00 1.00	9.00 0.33 3.00 1.00 3.00 0.33 7.00 0.33
--	--	--	--	--	--	--	--	--	--	--

AGGREGATION -- AB-PRIME MATRIX:

1.00	0.76	1.54	1 48	0.62	1 53	2 08	1.61	2 01	1.42	1.51
1.32	1.00	1.19			2.56		1.62		1.74	2.26
0.65	0.84	1.00	0.83	0.52			1.71		0.98	1.44
0.63	0.38	1.21	1.00	0.38	1.34	1.86	1.57	1.84	0.98	1.11
$1 \cdot \epsilon r$	1.80				3.10	3.50	1.95	3.23	2.21	1.92
0.65	6.39	0.60				1.75	0.94	1.93	0.60	0.80
0 43	0.74	0.59	0.54	0.29	0.57	1.00	0.54	1.13	0.41	0.50
0 , αP	G. C.	0.59	0.64	0.51	1.06	1.85	1.00	1.85	0.67	1.15
0.50	0 23	0.43	0.54	0.51	0.52	0.89	0.55	1.00	0.37	0.50
5.71	0.52	1.02	1.02	0.45	1.60	2.41	1.50	2.73	1.00	1.01
w.bb	0 . 444	0.70	0.90	0.52	1.24	2.01	0.87	2.02	0.99	1.00

NORMALIZED AB-PRIME MATRIX:

3.11					0.09				0.12	0.11
6 15	0.14	0.14	0.20	0.10	0.16	0.17	0.12	0.15	0.15	0.17
0 07	$^{ m C}$, 1.1	0.09	$\theta = 0.6$	0.09	0.10	0.11	0.17	0,10	0.09	-9.11
0.08	0 0.5	0.11	0.03	0.07	c - cs	0.08	0.11	0.08	0.09	0.08
0.18	0.25	0.18	00	0.18	0 19	0.15	0.14	0 14	0.19	0.15
J. D.	0.05	0.05	0.06	0.06	0.06	0.07	0.07	0.08	0.05	0.00
0.05	0 03	0.04	0.04	0.05	() () () (4	ਹੈ. 04	0.06	0.05	n.Uu	0.04
0.03	0.08	() . P6	0.05	0.09	0.07	0.08	0.07	0.08	1.06	$\{09\}$
0.00	0.09	0.04	0.04	0.06	0.05	0.04	0.04	0.04	1.85	0.00
0.00	8.0 0	0.10	8.08	0.03	a = 1.0	9 10	0.11	0 10	0.00	D . 11 .
0.7	0.06	0.07	0.07	0.10	0.08	0.08	0 00	0.09	0.09	0.08

SCALE VALUES:

Rapid Runway Repair	0.1772
Cargo Handling Battalion	0.1478
Naval Station Communication (AMCC Van)	0.1100
P-3C Intermediate Support Facility	0.0971
Aviation Tank Farm	0.0914
Tank Farm (medium, DFM & JP-5)	0.0827
Naval Overseas Air Cargo Terminal	0.0760
P-3A/B Intermediate Support Facility	0.0719
High Speed Fuel Dispensing System	0.0634
Casualty Staging Unit	0.0414
Blood Bank	0.0412

The Analytical Hierarchy Process described an additional measurement not included in the Constant Sum Method. When making pairwise comparisons, the possibility exists for a judge to rate item A over item B and rate item B over item C, but then to rate item C over item A, which is an inconsistent comparison. The consistency ratio in the Analytical Hierarchy Process measures the extent to which judges contradicted themselves in the way. Consistency ratio values of 0.1 or less are considered to be acceptable. The judges ratings from Survey 2 were computed to have a consistency ratio of 0.05849, a highly consistent result.

APPENDIX E. JUDGES' COMMENTS FROM SURVEYS

Answers to the Question: Did you have any difficulty understanding the scenario presented? If so, please comment:

Does not specify whether Host Nation Support arrangements, in place or being negotiated, are to be considered. Also not clear whether "theater specific" response was desired...

Not enough detail as to our concept of ops, enemy actions, attrition, Host Nation Support, etc., etc., etc.,

Answers to the Question: Would you have preferred that the situation be described differently? If so, how?

Since most of my experience relates to Europe, it was difficult to try to restrict choices...

Specify "come as you are" or "assume you have everything you need to complement Host Nation Support."

A more detailed scenario would have restricted the amount of imagination required.

Requirements for the ABFCs should have been identified/related to a specific OPLAN.

Answers to the Question: Did you have any difficulty understanding the instructions for giving responses? If so, explain:

The instructions were clear but I have a very sketchy knowledge of the ABFC requirements for its CINC plans. This made all choices suspect.

Answers to the Question: Did you feel more comfortable responding to one (survey) than the other? If so, which one and why?

I felt more comfortable with the first.

First one -- not comparing apples and oranges per se.

Survey #1 is easier to follow.

Second survey was very long.

Survey 1 -- more realistic.

Survey I is easier. Survey 2 seemed to run together after one page. I felt like I had compared some of the choices before.

The second one is very dependent on theater, threat and operations at the time of the event. The priorities on an ABFC will change dependent ou scenario.

More comfortable with Survey #2 -- not as scenario dependent.

Survey #1 was easier to follow.

Survey 1. Choices were clear cut, without the requirement to balance impact of loss of one ABFC over another.

It was easier to respond to the first due to the fact that it is more valid to respond to an ABFC's value to an operation vice its relative merits within an operation.

Survey 1 was easier. You didn't have to "quantify" your guesses.

Answers to the Question: Did one method seem more realistic for rating the value of ABFCs? If yes, which one and why?

Survey 1. Asks "real life" questions.

First method since (it was) more general. Comparing one against the other can go either way depending on specific geographic location.

As with anything, value is relative. We are trying to hedge our bets by determining which ABFCs are more important. The answer is always going to be a moving target.

The first, it seemed to allow a broader general perception of the importance of a given ABFC without a strict comparison.

The second -- the comparative values -- one against the other -- causes more thought of each one's relative worth.

(Survey 1) is more realistic -- comparing non-like items (as in Survey 2) is unrealistic in some cases.

Comparison: provides for greater subjectivity and causes rater to provide a respective value of his selection.

Survey #1. Compared each item to itself rather than to other items which in many cases were not related.

To try to rate one ABFC versus another is difficult due to different functions they perform. Contribution to war effor (prioritize which I need most) would be better method, i.e., #1, #2, etc.

Scenario is too general for a realistic rating of Survey 2.

Survey 2 is better. I had to compare each choice and the effects it would have at that time of war.

2nd -- comparison values vice absolute.

Survey 1, if one takes the results of this survey for POMing (Program Objectives Memorandum: a process in the Federal budget) ABFCs, it could be serious mistake. The 4040 report that the CINCs (Commanders-in-Chief) ituation Reports) should be used.

Survey 2. In a survey and was scenario, preceded by an extended period of resource austerity and the increase than one ABFC may not be available or up to

strength, which we a coessitate some hard choices.

Miscellaneous Colans ats:

Assume survey intermed theater requirement mission degradation what fleets are structured to the control of the

to be subjective. Only objective method to determine to have all existing in-theater resources related to numerate the deficiencies and prioritize them as to an match ABFCs against the deficiency list. This is d to do when submitting ABFC priorities to OPNAV aval Operations).

I found Survey I easier, but I do not know that it is more realistic.

...These questionnaires require a fairly detailed knowledge of the CINC OPLANS (Commander-in-Chief Operations Plans) and the resources available for carrying them out. The answers given are a 'guess', at best. These are not good surveys unless the person filling them out has the necessary background. For example, the number of P-3 A/B aircraft in the OPLAN and the current facilities available: the fueling capability of anticipated air facilities: etc.

I have evaluated it e ABFCs from the perspective of (one particular Commander-in-Chief, who has particular area repossibilities). I have assumed Host Nation Support to be as currently averable, with a sufficient number of ABFCs to compensate for deficiencies in Host Nation Support. For example, (in some areas),... fuel ABFCs would not be needed: thus, their low priority. Also, (one particular ABFC) is important to me because that is my key function. (A particular Commander-in-Chief) might rate it lower than I and put something else higher. Life-support ABFCs always rate highest priority in my opinion.

Most of the ABFCs are important but I have serious reservations they would be functional on D+10. The AFGE would still be off-loading and in a global war, the fighting would still be hot and heavy.

...I worry that this survey could be used for POM issues. As stated, the CNO should use the 4040 report and the CINC's SITREPS.

...Survey #2 ends up comparing ABFCs when the scenario is not given in detail. It is hard to say medical is less important than P-3C maintenance when taking care of our men is so important. However, if we don't have the support for our forces, the casualties are going to be even higher. The point is that the priority of any ABFC can and does change because of factors such as:

- 1) Theater of operations
- 2 Available inter-service support
- 3, War time Host Nation Support
- 4) Threat
- 5) Concept of Ops, which can change dependent on timing, threat, mission, etc.
- 6) Forces to be supported changes

Logistics is not as easy as making a formula and letting a computer do the work. One must look at the "big picture" to see what is required for that mission, area, and forces. Each location is different, each scenario is different.

I'm not sure the results of this survey will provide a valid indication of relative merits of ABFCs. ...I think you need to focus on a small set of related ABFCs; example: P-3 support; and do some in-depth ops analysis of their capabilities in a 6-month "campaign," similar to (another project being worked). I don't think it is possible to rank ABFCs without this type of analysis.

My response may have been different if I knew the (specific) scenario in which these ABFCs were being utilized.

LIST OF REFERENCES

- 1. Chief of Naval Operations Publication 41P3B, <u>Table of Advanced Base Functional Components (with abridged initial outfitting lists)</u>, Navy Department, Washington, DC, June 1987.
- 2. Chief of Naval Operations Instruction 4040.39A, Navy Advanced Base Functional Component (ABFC) Planning System. Office of the Chief of Naval Operations (OP-41R), Washington, DC, October 1985.

- 3. Lindsay, Glenn F., "On Constructing Interval Scales From Categorical Judgments," Unpublished paper, Naval Postgraduate School, Monterey, CA, September 1981.
- 4. Lindsay, Glenn F., "Scaling with the Constant Sum Method," Unpublished paper, Naval Postgraduate School, Monterey, CA, February 1980.
- 5. Saaty, Thomas L., <u>The Analytical Hierarchy Process: Planning, Priority Setting, Resource Allocation</u>, McGraw-Hill Book Co., 1980.
- 6. Crawford, Paul M., <u>Dynamic Study of Factors Impacting on Combat Power</u>, M.S. Thesis. Naval Postgraduate School, Monterey, CA, March 1988.
- 7. SYSCON Corporation, State of the Art Contingency Analysis (SOTACA)
 Analyst's Guide to Theory, Joint Chiefs of Staff Modern Aids to Planning
 Program (MAPP), Preliminary Draft II, June 1986.
- 8. Saaty, Thomas L., <u>Decision Making for Leaders</u>, Lifetime Learning Publications, 1982.

INITIAL DISTRIBUTION LIST

		No. Copies
1.	Defense Technical Information Center Cameron Station Alexandria, VA 22304-6145	2
2.	Defense Logistics Studies Information Exchange U.S. Army Logistics Management Center Fort Lee, VA 23801	2
3.	Library, Code 0142 Naval Postgraduate School Monterey, CA 93943-5002	2
4.	Deputy Chief of Naval Operations (Logistics) (OP-04) Navy Department Washington, DC 20350-2000	1
5.	Deputy Chief of Naval Operations (Logistics) (OP-40) Navy Department Washington, DC 20350-2000	3
6.	Deputy Chief of Naval Operations (Logistics) (OP-41R) ATTN: CDR R. Miller, USN Navy Department Washington, DC 20350-2000	1
7.	Deputy Chief of Naval Operations (Logistics) (OP-44R) ATTN: CAPT L. Wellborn, USN Navy Department Washington, DC 20350-2000	1
8.	Office of the Chief of Naval Operations (OP-743D) ATTN: COL N. F. Mitchell, USMC Navy Department Washington, DC 20350-2000	1
9.	Office of the Chief of Naval Operations (OP-372F) ATTN: COL F. T. Klabough, USMC Navy Department Washington, DC 20350-:2000	1
10.	Office of the Chief of Naval Operations (OP-0941CP) ATTN: Mr. Brady Navy Department Washington, DC 20350	1

11.	Commander-in-Chief U.S. Atlantic Fleet (Code N521) ATTN; CDR D. Erickson, USN Norfolk, VA 23511-6001	1
12.	Commander-in-Chief U.S. Naval Forces, Europe (Code N416) FPO New York, NY 09510-0151	1
13.	Commander-in-Chief U.S. Pacific Fleet (Code 406) ATTN: Mr. J. Zier Pearl Harbor, HI 96860	1
14.	Commander U.S. Naval Forces Central Command (Code N40) ATTN: LCDR W. Dempsey, USN Pearl Harbor, HI 96860	1
15.	Commander Military Sealift Command ATTN: CAPT J. Williams, USN Washington, DC 20398-5100	1
16.	Commander Naval Logistics Command, U.S. Pacific Fleet ATTN: CAPT N. Murphy, USN Pearl Harbor, HI 96860-7050	1
17.	Commander Naval Supply Systems Command (SUP-0321B) ATTN: CDR C. Lum, USN Naval Supply Systems Command Headquarters Washington, DC 20376-5000	1
18.	Commandant Headquarters, U.S. Marine Corps (I & N, LOP-1) ATTN: LTC M. Trimble, USMC Washington, DC 20380	1
19.	Commander Marine Corps Combat Development Command MAGTF Warfighting Center (Code C09) ATTN: CCL L. Edwards, USMC Quantico, VA 22134-5001	1
20.	Commander Marine Corps Development & Education Command Deputy for Education (Code C0924) ATTN: MAJ P. Balash, USMC Quantico, VA 22134-5050	1

21.	Commander Combat Logistics Group ONE (CLG-1 SUPO) ATTN: CDR J. Jennings, USN Building 221-2W Naval Supply Center Oakland, CA 94625	2.
22.	Commander Combat Logistics Group TWO FPO New York, NY 09501-5310	3
23.	Dr. Samuel H. Parry, Code 55Py Department of Operations Research Naval Postgraduate School Monterey, CA 93943	3
24.	CAPT Wayne P. Hughes, Jr., USN (Ret.), Code 55HI Department of Operations Research Naval Postgraduate School Monterey, CA 93943	1
2 5.	Dr. David A. Schrady, Code 55So Department of Operations Research Naval Postgraduate School Monterey, CA 93943	1
26.	Dr. Glenn F. Lindsay, Code 55Ls Department of Operations Research Naval Postgraduate School Monterey, CA 93943	1
27.	Dr. Thomas P. Moore, Code 54Mr Department of Operations Research Naval Postgraduate School Monterey, CA 93943	1
28.	Dr. Dan C. Boger, Code 54Bo Department of Operations Research Naval Postgraduate School Monterey, CA 93943	1
29.	CDR Mark L. Mitchell, Code 55Mi Department of Operations Research Naval Postgraduate School Monteney, CA 93943	1
30.	LCDR Linda A. Guadalupe, USN Navy & Marine Corps Intelligence Training Center Building 420 Dam Neck Virginia Beach, VA 23461-5575	2